

GU24 COVERED CFL



GU 24 Base R30 Reflector CFL

Nominal Wattage	Overdrive Model #	Item Description & CCT	Initial Lumen	Av Rated Life (hrs)	Diameter inch / mm	Length inch / mm	Pack Master	Item #
15	● 15W/ODGGU	15W Globe CFL GU24 Base - Soft White	740	10,000	3.3 / 84	4.5 / 113	12	127
15	● 15W/ODAGU	15W A Shape CFL GU24 Base - Soft White	800	10,000	2.6 / 67	4.5 / 113	12	126
15	● 15W/ODR30GU	15W R30 Reflector CFL GU24 Base - Soft White	650	10,000	3.7 / 95	4.5 / 113	12	128

- Approved under version 4.2 RLF

Applications

15W/ODGGU

15W/ODAGU

15W/ODR30GU



PENDANT FIXTURES



VANITY STRIP



WALL SCONE



PENDANT FIXTURES



CEILING



CEILING FAN



PENDANT FIXTURES



RECESSED CANS



TRACK LIGHTING



TABLE/ FLOOR LAMPS



READING LAMP



OUTDOOR COVERED



Features

- 10,000 hour average rated life reduces relamping & related costs
- Rare earth tri-phosphor with 80 plus CRI for better performance
- High Luminous Efficacy
- 75% Lower Power Consumption over incandescent bulbs
- Available in various color temperature
- Compact in Size and fits most applications

Notes

- Not Dimmable
- Available in various color temperature also (upon request)
- Dimension with + 0.1 inch tolerance