

**MR-16 JR 12V & 24V - EUROSTAR™ SERIES**

- Only for Use in Approved Halogen Fixtures
- 2 inch Diameter Dichroic Coated Reflector
- 2-Pin & Double Contact Bayonet Base
- 12 & 24 Volts
- Available with Front Glass Cover (FG)
- Consistent Color
- Up to 60 Degree Beam



Watts	Ushio Ordering Code	Ushio Lamp Code	Dimension	Filament	Beam		Color Temp K	Avg Life h	Burn Position	Case Qty
			MOL (A)	Type	Angle	Max CP cd				
<b>EUROSTAR™ 24V, 2-Pin Base – GU5.3</b>										
20	1001112	JR24V-20W/SP12	1.77	C-6	12°	3500	2900	2500	Univ	50
20	1001113	JR24V-20W/SP12/FG	1.78	C-6	12°	3500	2900	2500	Univ	50
20	1001114	JR24V-20W/FL36	1.77	C-6	36°	600	2900	2500	Univ	50
20	1001115	JR24V-20W/FL36/FG	1.78	C-6	36°	600	2900	2500	Univ	50
35	1003110	JR24V-35W/SP12	1.77	C-6	12°	4600	2900	3500	Univ	50
35	1001119	JR24V-35W/SP12/FG	1.78	C-6	12°	4600	2900	3500	Univ	50
35	1003111	JR24V-35W/NFL24	1.77	C-6	24°	1600	2900	3500	Univ	50
35	1001117	JR24V-35W/NFL24/FG	1.78	C-6	24°	1600	2900	3500	Univ	50
35	1003112	JR24V-35W/FL36	1.77	C-6	36°	900	2900	3500	Univ	50
35	1001121	JR24V-35W/FL36/FG	1.78	C-6	36°	900	2900	3500	Univ	50
50	1003113	JR24V-50W/SP12	1.77	C-6	12°	7000	2950	4000	Univ	50
50	1001125	JR24V-50W/SP12/FG	1.78	C-6	12°	7000	2950	4000	Univ	50
50	1003114	JR24V-50W/NFL24	1.77	C-6	24°	2900	2950	4000	Univ	50
50	1001123	JR24V-50W/NFL24/FG	1.78	C-6	24°	2900	2950	4000	Univ	50
50	1003115	JR24V-50W/FL36	1.77	C-6	36°	1600	2950	4000	Univ	50
50	1001127	JR24V-50W/FL36/FG	1.78	C-6	36°	1600	2950	4000	Univ	50
75	1003281	JR24V-75W/FL36/FG	1.78	C-6	36°	2500	2900	3000	Univ	50
<b>12V, 2-Pin Base – GX5.3</b>										
42	1000461	EYR, JR12V-42W/SP12	1.81	CC-6	12°	9000	3000	4000	Univ	10
42	1000462	EYS, JR12V-42W/NFL23	1.81	CC-6	23°	2800	3000	4000	Univ	10
42	1000460	EYP, JR12V-42W/FL38	1.81	CC-6	38°	1400	3000	4000	Univ	10
65	1000595	FPA, JR12V-65W/SP13	1.81	CC-6	13°	11500	3050	4000	Univ	10
65	1000596	FPB, JR12V-65W/FL38	1.81	CC-6	38°	2000	3050	4000	Univ	10
<b>Double Contact Bayonet Base – BA15d</b>										
50	1001685	FNV/BA, JR12V-50W/BA/WFL60	2.20	C-8	60°	—	3000	4000	Univ	50

All dimensions shown in inches unless otherwise noted.

