


IN-WALL TIMERS

A500 AND C500 SERIES IN-WALL SPRING WOUND SHUT DOWN TIMERS



METAL WALLPLATE INCLUDED

FITS DECORATOR OR STANDARD SWITCHPLATE (NOT SUPPLIED). IVORY, WHITE AND ALMOND COLORS

APPLICATIONS

- Control whole house/ventilating fans, appliances, heat lamps, lighting, thermostats.

FEATURES & OPERATION:


Unit is mechanically spring wound, requiring no electricity to operate. Switch contacts are made when knob is rotated and break circuit at the end of a timed cycle, thereby turning OFF load. **CAUTION:** This timer is not to be used in precision timing applications where inaccurate timing could have dangerous consequences (i.e., sun lamp, sauna, etc.)

RATINGS

125VAC, 20 AMP inductive/resistive
125VAC, 7 AMP Tungsten
125VAC, 1 HP



USING DECORATOR SWITCHPLATE



USING STANDARD SWITCHPLATE



TIME CYCLE	METAL FACEPLATE			IVORY FACEPLATE			WHITE FACEPLATE			ALMOND FACEPLATE	
	WITH HOLD	WITHOUT HOLD	UPC CODE	WITH HOLD	WITHOUT HOLD	UPC CODE	WITH HOLD	WITHOUT HOLD	UPC CODE	WITHOUT HOLD ONLY	UPC CODE
5 minutes		C505M	15500		A505M	15012		A505MW	15112		
0-15 minutes	C515MH		15502	A515MH		15020	A515MHW		15120		
0-15 minutes		C515M	15501		A515M	15013		A515MW	15113	A515MA	15127
0-30 minutes	C530MH		15504	A530MH		15021	A530MHW		15121		
0-30 minutes		C530M	15503		A530M	15014		A530MW	15114	A530MA	15128
0-60 minutes	C560MH		15506	A560MH		15022	A560MHW		15122		
0-60 minutes		C560M	15505		A560M	15015		A560MW	15115	A560MA	15129
0-2 hours		C502H	15507		A502H	15016		A502HW	15116		
0-4 hours		C504H	15509		A504H	15017		A504HW	15117		
0-6 hours	C506HH		15512	A506HH		15025	A506HHW		15125		
0-6 hours		C506H	15511		A506H	15018		A506HW	15118		
0-12 hours	C512HH		15514	A512HH		15026	A512HHW		15126		
0-12 hours		C512H	15513		A512H	15019		A512HW	15119		

M500 SERIES IN-WALL MOTOR OPERATED SHUT DOWN TIMERS

APPLICATIONS

- Control whole house / ventilating fans
- Control air conditioning
- Control heat lamps

RATINGS

125VAC, 60Hz, 15A Resistive
& General Purpose,
125VAC, 1250W Tungsten
125VAC, 1/2 HP

FEATURES

- Ideal for applications where quiet operation is desired
- Units can be turned ON or OFF manually for temporary or permanent control.
- Choice of white or almond color
- Choice of 60 minute or 12 hour timing
- Requires neutral wire.
- WHITE OR ALMOND WALLPLATE, WIRE CONNECTORS AND MOUNTING SCREWS ARE INCLUDED

CHOICE OF WHITE OR ALMOND COLORS!



CATALOG NO	UPC CODE	TIME CYCLE	COLOR
M560MW	10115	60 MIN	WHITE
M560MA	10118	60 MIN	ALMOND
M512HW	10116	12 HOURS	WHITE
M512HA	10119	12 HOURS	ALMOND

OPERATION

To set the time duration required, rotate the knob, which causes the switch contacts to be made. The electric motor then takes over and breaks the circuit at the end of the time cycle, thereby turning OFF load. **CAUTION:** This timer is not to be used in precision timing applications where inaccurate timing could have dangerous consequences (i.e., sun lamp, sauna, etc.)