

# Decora® Universal Dimmers







**LED Compatibility Chart** 

Manufacturer	Bulb Model	Wattage	Color Temperature	Photo	Performance Rating	Turn on at Min Level?	Qty of Bulbs	Dimming Range (Min Load) 1%-100%
ECOSMART	PAR38 LED	18W	3000K		Better	Υ	1-2	1%
	CREE CR6 Recessed Downlight	10.5W	2700K	O.	Best	Y	1-8	1%
FEIT	Dimmable LED Candelabra	3.5W	3000K	A	Best	Y	1-7	1%
PHILIPS	EnduraLED A19	8W	2700K		Best	Y	1-8	1%
		7W	2700K		Best	Y	1-8	2%
		12.5W	2700K		Best	Υ	1-8	6%
	EnduraLED PAR20 Indoor Flood	7W	2700K, 3000K, 4200K		Best	Y	1-7	1%
	EnduraLED PAR38 Indoor Flood	16W	2700K, 3000K, 4200K	-	Better	Y	1-8	10%
		17W	2700K, 3000K, 4200K		Better	Y	1-8	8%
	EnduraLED PAR30S Indoor Flood	11W	2700K, 3000K, 4200K		Better	Y	1-8	8%
		12W	2700K, 3000K, 4200K		Best	Y	1-8	8%



Manufacturer	Bulb Model	Wattage	Color Temperature	Photo	Performance Rating	Turn on at Min Level?	Qty of Bulbs	Dimming Range (Min Load) 1%-100%
PHILIPS	AmbientLED A19 Soft White	7W	2700K		Best	Y	1-8	2%
	AmbientLED PAR30L Indoor Flood	12W	3000K		Better	Y	1-8	8%
	AmbientLED PAR38 Indoor Flood	17W	3000K		Better	Y	1-8	8%
	EuduralLED Candle	3W	2700K		Better	Y	1-8	6%
SYLVANIA	ULTRA LED PAR30 11PAR30, 15PAR30LN, 18PAR30LN	11W	2700K, 3000K		Best	Y	1-8	11%
		15W	2700K, 3000K	•	Better	Y	1-8	3%
		18W	3000K		Better	Y	1-8	9%
	ULTRA LED A-Line LED8A	8W	2700K		Best	Y	1-8	2%
	ULTRA RT6 LED Recessed Downlight Kit	11W	3000K	3	Best	Y	1-8	6%
	ULTRA LED PAR38	18W	2700K, 3000K, 4000K	· ·	Better	Y	1-8	6%
		24W	3000K		Best	Y	1-8	12%



Manufacturer	Bulb Model	Wattage	Color Temperature	Photo	Performance Rating	Turn on at Min Level?	Qty of Bulbs	Dimming Range (Min Load) 1%-100%
TOSHIBA	E-CORE Dimmable LED PAR20	9W	2700K, 3000K	9	Better	Y	2-8	6%
	E-CORE Dimmable LED PAR30 Short Neck and Long Neck	16.3W	2700K, 3000K, 4000K		Best	Y	1-8	6%
	E-CORE Dimmable LED PAR38	20.3W	2700K, 3000K, 3500K, 4000K	9	Better	Y	1-8	15%
VERBATIM	A19 LED	9W	2700K, 3000K	¥	Best	Y	2-8	5%
	PAR20 LED	9W	2700K, 3000K		Best	Y	1-8	1%
		9.3W	2700K, 3000K		Best	Y	1-2	8%
	PAR30 LED	14W	2700K, 3000K	9	Best	Y	1-8	1%
		14.7W	2700K, 3000K		Best	Y	1-3	1%
	PAR38 LED	17W	2700K, 3000K	9	Best	Y	1-8	1%
		19.5W	2700K, 3000K		Best	Y	1-4	1%

- Better: Bulbs will dim, flickering may be present but not significant and diminishes with manual adjustment of slide.
  Best: Starts at low end, dimming range similar to incandescent, no observable flickering

1. Y: The dimmer will start bulbs with the slide bar at the lowest position. The dimmer may require the user to preset the minimum light level for starting. 2. N: Bulbs will not start with the slide bar at the lowest position.

This represents the quantity of bulbs tested for compatibility purposes and is not intended to indicate the maximum load. The maximum load is limited to 150W for LED and CFL. In some cases, the minimum number of bulbs was increased in order to achieve better performance.

NOTE: LED/CFL/Incandescent dimmers - have been evaluated per the UL standard for specified dimmable LED, CFL and incandescent loads.

All products and trademarks are the property of their respective owners.

## Visit our Website at: www.leviton.com/universal

 $\hbox{@}$  2012 Leviton Manufacturing Co., Inc. All rights reserved. Subject to change without notice.

G-8693/A12-dp