

STYLE NO: 22490 Parts and hardware list

1	Screw Collar Nut	2PCS
2	Nipple	1PC
3	8-32 Screws	2PCS
4	Mounting Plate	1PC
5	Green Ground screw	1PC
6	Wire Nut	5PCS

Please make sure that you have all the parts indicated before you begin assembling this item.

Please Read Wiring Instruction before you begin assembling and installing your chandelier lamp.

WARNING: BEFORE INSTALLING. make sure the electricity supply is shut off to avoid a possible electric shock

Assembly Instruction

- 1. Take the parts carefully out of the carton, place them on a flat surface, and make sure that the parts will not be damaged
- 2. Attach the Crossbar to the Outlet Box by using two 8-32 Screws (See Figure 1)
- 3. Connect the black 120V input wire from the Ballast to the black supply wire or smooth wire(s). (See Figure 3)
- 4. Connect the white 120V input wire from the Ballast to the white supply wire or ribbed wire(s). (See Figure 3)
- 5. Connect the arbitrarily 12V output wire from the Ballast to the black wire or smooth wire from the fixture. (Use wirenuts provided) (See Figure 3)
- 6. Connect the arbitrarily 12V output wire from the Ballast to the white wire or ribbed wire from the fixture. (Use wirenuts provided) (See Figure 3)
- 7. Connect the fixture ground wire to the outlet box ground wire . (Use wirenuts provided).
- 8. After the wires are connected, carefully place them inside the Outlet Box (See Figure 1)
- 9. Mount fixture by aligning mounting holes in wall plate (D) with mounting screws and threading Ball Nuts (E) onto mounting screws. Tighten to fixture hold wall plate (D) in place against wall . (mounting screws may require adjustment).
- 10. Install the G4 bulb (B) to the socket. (Bulb Included).
- 11. Attach the Crystal (C) to the Tube (A) as the same direction of lamp cup and make sure it stable.



STYLENO: 22490

Assembly Instruction

