

#### 46761 - F54W/T5/841/ECO

GE Ecolux® Starcoat® T5


• Passes TCLP, which can lower disposal costs.

a product of

# ecomagination







### **CAUTIONS & WARNINGS**

#### Caution


- Lamp may shatter and cause injury if broken
- Wear safety glasses and gloves when handling lamp.
- Do not use excessive force when installing lamp.

#### Warning


- Risk of Electric Shock
- Turn power off before inspection, installation or removal.

# **GRAPHS & CHARTS**

**Graphs\_Lumen Maintenance** 



# **Graphs\_Lamp Mortality**



#### **GENERAL CHARACTERISTICS**

Lamp Type Linear Fluorescent - Straight

Bulb

Base Miniature Bi-Pin (G5)

Rated Life 30000.0 hrs

Rated Life (rapid start) @ Time 30000.0 @ 3.0/36000.0 @

12.0 h

Soda lime **Bulb Material** Starting Temperature (MIN) -20.0 °C

LEED-EB MR Credit 18 picograms Hg per mean

lumen hour

Additional Info TCLP compliant **Primary Application** Full Wattage

#### PHOTOMETRIC CHARACTERISTICS

**Initial Lumens** 5000.0 Mean Lumens 4600.0 Nominal Initial Lumens per Watt 92 4100.0 K Color Temperature Color Rendering Index (CRI) 85.0 S/P Ratio (Scotopic/Photopic 1.7 Ratio)

# **ELECTRICAL CHARACTERISTICS**

Wattage Voltage 117.0

520 V @ 10 °C Open Circuit Voltage (rapid

start) Min @ Temperature

Cathode Resistance Ratio - Rh/ 4.25 Rc (MIN) Cathode Resistance Ratio - Rh/ 6.5

Rc (MAX)

Lamp Current 460.0 mA Current Crest Factor (MAX) 1.7

# **DIMENSIONS**

Maximum Overall Length 45.2000 in(1148.1 mm)

(MOL)

Nominal Length 45.200 in(1148.1 mm) Bulb Diameter (DIA) (MAX) 0.670 in(17.0 mm) Bulb Diameter (DIA) 0.625 in(15.9 mm) Max Base Face to Base Face 45.240 in(1149.1 mm)

(A)

Face to End of Opposing Pin 45.420 in(1153.7 mm)

(B) (MIN)

Face to End of Opposing Pin 45.520 in(1156.2 mm)

(B) (MAX)

## **PRODUCT INFORMATION**

**Product Code** 46761

Description F54W/T5/841/ECO

Standard Package Case

Standard Package GTIN 10043168467619

Standard Package Quantity 40 Sales Unit Unit

No Of Items Per Sales Unit 1 No Of Items Per Standard 40

Package

UPC 043168467612

# **Graphs\_Spectral Power Distribution**

