



CERTIFIED GREEN

CLEAR VISION SUPREME™

High Performance Forward Lighting

FEATURES

Clear Vision Supreme™ premium halogen headlamps feature SoLux™ Technology that produces up to 80% brighter and 50% whiter light, as well as the longest beam of any DOT legal headlamp.

SoLux is a patented technology that simulates real daylight better than any other headlamp. No other lamp can do what SoLux does to improve visibility, contrast and safety while driving.

CLEAR VISION
Supreme



Original Equipment



Clear Vision Supreme™

Clear Vision® Supreme									
Ordering Code	Watts	Volts	Shape	Base	Filament	Lumens	MOL	MOD	Life Hours
880CVSU-BP	27	12.8	T-3 1/4	Axial Prefocus (PG13)	C-6		2.68/68.1	0.42/10.7	500
881CVSU-BP	27	12.8	T-3 1/4	Right-Angle Prefocus, (PGJ13)	C-6		2.68/68.1	0.42/10.7	500
885CVSU-BP	50	12.8	T-3 1/4	Axial Prefocus (PG13)	C-6	1320	2.68/68.1	0.42/10.7	500
889CVSU-BP	27	12.8	T-3 1/4	Right-Angle Prefocus, (PGJ13)	C-6		2.68/68.1	0.42/10.7	500
893CVSU-BP	37.5	12.8	T-3 1/4	Axial Prefocus (PG13)	C-6		2.68/68.1	0.42/10.7	500
894CVSU-BP	37.5	12.8	T-3 1/4	Right-Angle Prefocus, (PGJ13)	C-6		2.68/68.1	0.42/10.7	500
896CVSU-BP	37.5	12.8	T-3 1/4	Right-Angle Prefocus, (PGJ13)	C-6		2.68/68.1	0.42/10.7	500
899CVSU-BP	37.5	12.8	T-3 1/4	Axial Prefocus (PG13)	C-6		2.68/68.1	0.42/10.7	1900
9003/H4CVSU-BP	60/55	12.8/12.8	T-5	Axial Prefocus, HB2 (P43t38)	C-8/C-8	1545/955	3.62/92.0	0.65/16.5	180/120
9003/H4CVSU2	60/55	12.8/12.8	T-5	Axial Prefocus, HB2 (P43t38)	C-8/C-8	1545/955	3.62/92.0	0.65/16.5	180/120
9004CVSU-BP	65/45	12.8/12.8	T-4 3/4	Axial Prefocus, HB1 (P29t)	C-6/C-6	1195/690	4.17/106	1.33/33.8	180/90
9004CVSU2	65/45	12.8/12.8	T-4 3/4	Axial Prefocus, HB1 (P29t)	C-6/C-6	1195/690	4.17/106	1.33/33.8	180/90
9005CVSU-BP	65	12.8	T-3 1/4	Right Angle Prefocus, HB3 (P20d)	C-8	1695	3.09/78.0	0.42/10.7	145
9005CVSU2	65	12.8	T-3 1/4	Right Angle Prefocus, HB3 (P20d)	C-8	1695	3.09/78.0	0.42/10.7	145
9005XSCVSU-BP	65	12.8	T-3 1/4	Axial Prefocus, HB3A (P20d)	C-8	1695	2.59/65.9	0.42/10.7	150
9005XSCVSU2	65	12.8	T-3 1/4	Axial Prefocus, HB3A (P20d)	C-8	1695		0.42/10.7	150
9006CVSU-BP	55	12.8	T-3 1/4	Right Angle Prefocus, HB4 (P22d)	C-8	1005	3.09/78.0	0.42/10.7	775
9006CVSU2	55	12.8	T-3 1/4	Right Angle Prefocus, HB4 (P22d)	C-8	1005	3.09/78.0	0.42/10.7	775
9006XSCVSU-BP	55	12.8	T-3 1/4	Axial Prefocus, HB4A (P22d)	C-8	1005	2.61/66.29	0.42/10.7	335
9006XSCVSU2	55	12.8	T-3 1/4	Axial Prefocus, HB4A (P22d)	C-8	1005	2.61/66.29	0.42/10.7	335
9007CVSU-BP	65/55	12.8/12.8	T-4 3/4	Axial Prefocus, HB5 (Px29t)	C-8/C-8	1345/1105	4.17/106	1.33/33.8	250/125
9007CVSU2	65/55	12.8/12.8	T-4 3/4	Axial Prefocus, HB5 (Px29t)	C-8/C-8	1345/1105	4.17/106	1.33/33.8	250/125
9008CVSU-BP	65/55	12.8/12.8	T-5	Axial Prefocus, H13 (P26.4t)	C-8/C-8	1510/1005	3.68/93.6	0.63/16.0	325/160
9008CVSU2	65/55	12.8/12.8	T-5	Axial Prefocus, H13 (P26.4t)	C-8/C-8	1510/1005	3.68/93.6	0.63/16.0	325/160
H11BCVSU-BP	55	13.2	T-3 1/4	Right Angle Prefocus, H11B (PGJY19-2)	CC-8	1345	2.63/66.8	0.43/10.8	1000
H11BCVSU2	55	13.2	T-3 1/4	Right Angle Prefocus, H11B (PGJY19-2)	CC-8	1345	2.63/66.8	0.43/10.8	1000
H155CVSU-BP	55	12	T-3 1/2	H1 Type (P14.5s)	C-8	1545	2.65/67.3	0.33/8.4	225
H155CVSU2	55	12	T-3 1/2	H1 Type (P14.5s)	C-8	1545	2.65/67.3	0.33/8.4	225
H355CVSU-BP	55	12	T-3 1/2	Prefocus Flanged, H3 (PK22s)	CC-6	1445	1.65/41.9	0.46/11.5	320
H355CVSU2	55	12	T-3 1/2	Prefocus Flanged, H3 (PK22s)	CC-6	1445	1.65/41.9	0.46/11.5	320
H755CVSU-BP	55	12.8	T-3 1/2	Axial Prefocus, H7 (PX26d)	C-8	1510	2.36/60.0	0.49/12.5	125
H755CVSU2	55	12.8	T-3 1/2	Axial Prefocus, H7 (PX26d)	C-8	1510	2.36/60.0	0.49/12.5	125
H1042CVSU-BP	42	13.2	T-4	Right Angle Prefocus, H10 (PY20d)	CC-8	840	3.17/80.5	0.47/11.8	775
H1042CVSU2	42	13.2	T-4	Right Angle Prefocus, H10 (PY20d)	CC-8	840	3.17/80.5	0.47/11.8	775
H1155CVSU-BP	55	13.2	T-3 1/4	Right Angle Prefocus, H11 (PGJ19-2)	CC-8	1345	2.64/67	0.43/10.8	310
H1155CVSU2	55	13.2	T-3 1/4	Right Angle Prefocus, H11 (PGJ19-2)	CC-8	1345	2.64/67	0.43/10.8	310

