

FEATURES

Power Vision PRO™ halogen headlamps feature a high performance tungsten filament that produces up to 50% brighter and 10% whiter light than the average lamp. More light on the road improves visibility and safety.

Unlike other competitive lamps, this enhanced performance is achieved without sacrificing life. Light hour ratings are the same as the original equipment lamp.

POWER VISION PRO™



Original Equipment



Power Vision PRO™

Power Vision PRO®									
Ordering Code	Watts	Volts	Shape	Base	Filament	Lumens	MOL	MOD	Life Hours
9003/H4PVP-BP	60/55	12.8/12.8	T-5	Axial Prefocus, HB2 (P43t38)	C-8/C-8	1545/955	3.62/92.0	0.65/16.5	280/200
9003/H4PVP2	60/55	12.8/12.8	T-5	Axial Prefocus, HB2 (P43t38)	C-8/C-8	1545/955	3.62/92.0	0.65/16.5	280/200
9004PVP-BP	65/45	12.8/12.8	T-4 3/4	Axial Prefocus, HB1 (P29t)	C-6/C-6	1195/690	4.17/106	1.33/33.8	220/110
9004PVP2	65/45	12.8/12.8	T-4 3/4	Axial Prefocus, HB1 (P29t)	C-6/C-6	1195/690	4.17/106	1.33/33.8	220/110
9005PVP-BP	65	12.8	T-3 1/4	Right Angle Prefocus, HB3 (P20d)	C-8	1695	3.09/78.0	0.42/10.7	185
9005PVP2	65	12.8	T-3 1/4	Right Angle Prefocus, HB3 (P20d)	C-8	1695	3.09/78.0	0.42/10.7	185
9005XSPVP-BP	65	12.8	T-3 1/4	Axial Prefocus, HB3A (P20d)	C-8	1695	2.59/65.9	0.42/10.7	320
9005XSPVP2	65	12.8	T-3 1/4	Axial Prefocus, HB3A (P20d)	C-8	1695	2.59/65.9	0.42/10.7	320
9006PVP-BP	55	12.8	T-3 1/4	Right Angle Prefocus, HB4 (P22d)	C-8	1005	3.09/78.0	0.42/10.7	635
9006PVP2	55	12.8	T-3 1/4	Right Angle Prefocus, HB4 (P22d)	C-8	1005	3.09/78.0	0.42/10.7	635
9006XSPVP-BP	55	12.8	T-3 1/4	Axial Prefocus, HB4A (P22d)	C-8	1005	2.61/66.29	0.42/10.7	330
9006XSPVP2	55	12.8	T-3 1/4	Axial Prefocus, HB4A (P22d)	C-8	1005	2.61/66.29	0.42/10.7	330
9007PVP-BP	65/55	12.8/12.8	T-4 3/4	Axial Prefocus, HB5 (P29t)	C-8/C-8	1345/1105	4.17/106	1.33/33.8	375/185
9007PVP2	65/55	12.8/12.8	T-4 3/4	Axial Prefocus, HB5 (Px29t)	C-8/C-8	1345/1105	4.17/106	1.33/33.8	375/185
9008PVP-BP	65/55	12.8/12.8	T-5	Axial Prefocus, H13 (P26.4t)	C-8/C-8	1510/1005	3.68/93.6	0.63/16.0	700/325
9008PVP2	65/55	12.8/12.8	T-5	Axial Prefocus, H13 (P26.4t)	C-8/C-8	1510/1005	3.68/93.6	0.63/16.0	700/325
H11BPVP-BP	55	13.2	T-3 1/4	Right Angle Prefocus, H11B (PGJY19-2)	CC-8	1345	2.63/66.8	0.43/10.8	1000
H11BPVP2	55	13.2	T-3 1/4	Right Angle Prefocus, H11B (PGJY19-2)	CC-8	1345	2.63/66.8	0.43/10.8	1000
H155PVP-BP	55	12	T-3 1/2	H1 Type (P14.5s)	C-8	1545	2.65/67.3	0.33/8.4	150
H155PVP2	55	12	T-3 1/2	H1 Type (P14.5s)	C-8	1545	2.65/67.3	0.33/8.4	150
H355PVP-BP	55	12	T-3 1/2	Prefocus Flanged, H3 (PK22s)	CC-6	1445	1.65/41.9	0.46/11.5	320
H355PVP2	55	12	T-3 1/2	Prefocus Flanged, H3 (PK22s)	CC-6	1445	1.65/41.9	0.46/11.5	320
H755PVP-BP	55	12.8	T-3 1/2	Axial Prefocus, H7 (PX26d)	C-8	1510	2.36/60.0	0.49/12.5	150
H755PVP2	55	12.8	T-3 1/2	Axial Prefocus, H7 (PX26d)	C-8	1510	2.36/60.0	0.49/12.5	150
H1042PVP-BP	42	13.2	T-4	Right Angle Prefocus, H10 (PY20d)	CC-8	840	3.17/80.5	0.47/11.8	775
H1155PVP-BP	55	13.2	T-3 1/4	Right Angle Prefocus, H11 (PGJ19-2)	CC-8	1345	2.64/67	0.43/10.8	330
H1155PVP2	55	13.2	T-3 1/4	Right Angle Prefocus, H11 (PGJ19-2)	CC-8	1345	2.64/67	0.43/10.8	330
H4656PVP	35/35	12.8	Rec 100x165	3 Contact Lugs	C-6/C-6		4.8/121		200/320
H6024PVP	65/35	12.8	PAR 56	3 Contact Lugs	C-6/C-6		5.0/127	7.0/178	150/450
H6054PVP	65/35	12.8	Rec 142x200	3 Contact Lugs	C-6/C-6		5.44/138		150/320

NOTES:
