

PRELIMINARY



Soraa Internal Report: IES LM79-08

Test results reported for:

Customer Reference P/N: **SR111-18-25D-830-03**

Manufacturing P/N: SR111-18-25D-830-03

Soraa AR111, G53/12V, 3000K, 80CRI, 18.5W, 25degree

Relevant Standards

IES LM-79

ANSI C78.377

IES PR-16

Soraa Lamp Lab

1.0 Description of test sample

Customer reference ID	SR111-18-25D-830-03
Manufacturer reference ID	SR111-18-25D-830-03
Lamp description	Premium 3000K 90CRI 18.5W 25 degree
Rated voltage	AC 12V
Rated power	18.5W
Nominal CCT	3000K




2.0 Results - Sphere Measurements

Test conditions	
Orientation	Horizontal
Stabilization time (min)	50-55
Correction factor applied	Self absorption correction
Sphere geometry	65" Sphere
	95% coating reflectance
	2pi geometry
Ambient temperature (°C)	25±1


Instrument				
	Instrument	Manufacture	Model	
Photometric	Spectrometer	Instrument systems	CAS 140T	
	Integrating sphere	Labsphere	65"	
	Standard lamp	Labsphere	CSFS-1400 lamp	
Electrical instrument	Power supply for standard lamp	Labsphere	LPS-150-0268	
	Power supply for aux lamp	Labsphere	LPS-100-0833	
	Power supply for test lamps	APT	Variplus 105	
	Power meter for test lamps	Chroma	66202	
Thermometer	Digital multimeter	YOKOGAWA	TY720	

Measurement results				
	Photometric		Electrical	
Total lumen (lm)	1315		Input voltage (V)	119.6
Luminous efficacy (lm/W)	71		Current (A)	0.156
Chromaticity coordinates	$u' = 0.2515$		Power (W)	18.5
	$v' = 0.5205$		pf	0.989
	$x = 0.4369$			
	$y = 0.4019$			
CCT (K)	3000			
CRI	86			
R9	16			
Duv				

Spectral power distribution




Chromaticity on CIE1931



CRI

R1	85
R2	96
R3	89
R4	85
R5	88
R6	97
R7	82
R8	61
R9	16
R10	94
R11	87
R12	86
R13	88
R14	94
Ra	86



WL (nm)	SPD(W/nm)	WL (nm)	SPD(W/nm)	WL (nm)	SPD(W/nm)	WL (nm)	SPD(W/nm)	WL (nm)	SPD(W/nm)
380	1.32E-04	421	1.44E-02	462	6.60E-03	503	1.26E-02	544	1.41E-02
381	1.30E-04	422	1.31E-02	463	6.77E-03	504	1.25E-02	545	1.43E-02
382	1.36E-04	423	1.17E-02	464	6.94E-03	505	1.26E-02	546	1.45E-02
383	1.30E-04	424	1.03E-02	465	7.07E-03	506	1.26E-02	547	1.46E-02
384	1.39E-04	425	9.16E-03	466	7.24E-03	507	1.26E-02	548	1.48E-02
385	1.42E-04	426	8.22E-03	467	7.43E-03	508	1.25E-02	549	1.50E-02
386	1.50E-04	427	7.33E-03	468	7.60E-03	509	1.25E-02	550	1.52E-02
387	1.57E-04	428	6.63E-03	469	7.81E-03	510	1.25E-02	551	1.54E-02
388	1.77E-04	429	6.04E-03	470	7.99E-03	511	1.25E-02	552	1.56E-02
389	1.93E-04	430	5.56E-03	471	8.15E-03	512	1.25E-02	553	1.59E-02
390	2.49E-04	431	5.14E-03	472	8.38E-03	513	1.25E-02	554	1.61E-02
391	3.36E-04	432	4.79E-03	473	8.56E-03	514	1.25E-02	555	1.63E-02
392	4.27E-04	433	4.51E-03	474	8.75E-03	515	1.24E-02	556	1.66E-02
393	5.71E-04	434	4.26E-03	475	8.95E-03	516	1.24E-02	557	1.68E-02
394	7.67E-04	435	4.10E-03	476	9.18E-03	517	1.24E-02	558	1.71E-02
395	1.05E-03	436	3.95E-03	477	9.37E-03	518	1.24E-02	559	1.74E-02
396	1.39E-03	437	3.82E-03	478	9.57E-03	519	1.24E-02	560	1.76E-02
397	1.85E-03	438	3.75E-03	479	9.79E-03	520	1.24E-02	561	1.80E-02
398	2.40E-03	439	3.73E-03	480	1.00E-02	521	1.24E-02	562	1.82E-02
399	3.11E-03	440	3.71E-03	481	1.02E-02	522	1.24E-02	563	1.85E-02
400	3.96E-03	441	3.79E-03	482	1.04E-02	523	1.24E-02	564	1.88E-02
401	5.01E-03	442	3.86E-03	483	1.06E-02	524	1.25E-02	565	1.91E-02
402	6.23E-03	443	3.94E-03	484	1.08E-02	525	1.25E-02	566	1.95E-02
403	7.56E-03	444	4.04E-03	485	1.10E-02	526	1.25E-02	567	1.97E-02
404	9.02E-03	445	4.15E-03	486	1.11E-02	527	1.25E-02	568	2.01E-02
405	1.08E-02	446	4.26E-03	487	1.13E-02	528	1.26E-02	569	2.04E-02
406	1.25E-02	447	4.40E-03	488	1.14E-02	529	1.26E-02	570	2.08E-02
407	1.41E-02	448	4.52E-03	489	1.16E-02	530	1.27E-02	571	2.11E-02
408	1.57E-02	449	4.67E-03	490	1.17E-02	531	1.27E-02	572	2.14E-02
409	1.70E-02	450	4.81E-03	491	1.19E-02	532	1.28E-02	573	2.17E-02
410	1.80E-02	451	4.95E-03	492	1.20E-02	533	1.29E-02	574	2.21E-02
411	1.87E-02	452	5.07E-03	493	1.21E-02	534	1.29E-02	575	2.24E-02
412	1.91E-02	453	5.24E-03	494	1.22E-02	535	1.30E-02	576	2.27E-02
413	1.92E-02	454	5.35E-03	495	1.22E-02	536	1.31E-02	577	2.30E-02
414	1.90E-02	455	5.56E-03	496	1.23E-02	537	1.32E-02	578	2.34E-02
415	1.89E-02	456	5.68E-03	497	1.24E-02	538	1.34E-02	579	2.36E-02
416	1.86E-02	457	5.83E-03	498	1.25E-02	539	1.35E-02	580	2.39E-02
417	1.81E-02	458	5.97E-03	499	1.25E-02	540	1.36E-02	581	2.42E-02
418	1.75E-02	459	6.14E-03	500	1.25E-02	541	1.37E-02	582	2.45E-02
419	1.67E-02	460	6.28E-03	501	1.26E-02	542	1.39E-02	583	2.48E-02
420	1.57E-02	461	6.44E-03	502	1.26E-02	543	1.40E-02	584	2.51E-02

Spectral Power Distribution

WL (nm)	SPD(W/nm)	WL (nm)	SPD(W/nm)	WL (nm)	SPD(W/nm)	WL (nm)	SPD(W/nm)	WL (nm)	SPD(W/nm)
585	2.53E-02	626	2.44E-02	667	1.15E-02	708	3.81E-03	749	1.13E-03
586	2.56E-02	627	2.42E-02	668	1.13E-02	709	3.71E-03	750	1.10E-03
587	2.58E-02	628	2.39E-02	669	1.10E-02	710	3.59E-03	751	1.08E-03
588	2.61E-02	629	2.36E-02	670	1.07E-02	711	3.50E-03	752	1.04E-03
589	2.62E-02	630	2.33E-02	671	1.05E-02	712	3.40E-03	753	1.01E-03
590	2.65E-02	631	2.30E-02	672	1.02E-02	713	3.30E-03	754	9.86E-04
591	2.67E-02	632	2.27E-02	673	9.96E-03	714	3.20E-03	755	9.57E-04
592	2.69E-02	633	2.24E-02	674	9.73E-03	715	3.12E-03	756	9.27E-04
593	2.70E-02	634	2.21E-02	675	9.48E-03	716	3.03E-03	757	8.99E-04
594	2.71E-02	635	2.17E-02	676	9.25E-03	717	2.95E-03	758	8.67E-04
595	2.73E-02	636	2.14E-02	677	9.01E-03	718	2.86E-03	759	8.47E-04
596	2.74E-02	637	2.11E-02	678	8.79E-03	719	2.79E-03	760	8.29E-04
597	2.75E-02	638	2.08E-02	679	8.56E-03	720	2.70E-03	761	7.95E-04
598	2.76E-02	639	2.05E-02	680	8.37E-03	721	2.62E-03	762	7.75E-04
599	2.77E-02	640	2.01E-02	681	8.12E-03	722	2.54E-03	763	7.51E-04
600	2.77E-02	641	1.97E-02	682	7.95E-03	723	2.48E-03	764	7.30E-04
601	2.78E-02	642	1.94E-02	683	7.72E-03	724	2.41E-03	765	7.15E-04
602	2.78E-02	643	1.91E-02	684	7.53E-03	725	2.33E-03	766	6.98E-04
603	2.78E-02	644	1.87E-02	685	7.32E-03	726	2.27E-03	767	6.71E-04
604	2.78E-02	645	1.84E-02	686	7.15E-03	727	2.20E-03	768	6.50E-04
605	2.78E-02	646	1.81E-02	687	6.93E-03	728	2.14E-03	769	6.28E-04
606	2.78E-02	647	1.77E-02	688	6.76E-03	729	2.07E-03	770	6.16E-04
607	2.77E-02	648	1.74E-02	689	6.57E-03	730	2.01E-03	771	6.02E-04
608	2.77E-02	649	1.71E-02	690	6.40E-03	731	1.95E-03	772	5.72E-04
609	2.76E-02	650	1.67E-02	691	6.23E-03	732	1.89E-03	773	5.61E-04
610	2.75E-02	651	1.64E-02	692	6.06E-03	733	1.84E-03	774	5.49E-04
611	2.75E-02	652	1.61E-02	693	5.88E-03	734	1.78E-03	775	5.33E-04
612	2.73E-02	653	1.58E-02	694	5.71E-03	735	1.72E-03	776	5.22E-04
613	2.72E-02	654	1.54E-02	695	5.55E-03	736	1.66E-03	777	5.00E-04
614	2.71E-02	655	1.51E-02	696	5.41E-03	737	1.63E-03	778	4.84E-04
615	2.68E-02	656	1.48E-02	697	5.27E-03	738	1.57E-03	779	4.83E-04
616	2.68E-02	657	1.45E-02	698	5.10E-03	739	1.52E-03	780	4.61E-04
617	2.66E-02	658	1.42E-02	699	4.97E-03	740	1.48E-03		
618	2.63E-02	659	1.38E-02	700	4.82E-03	741	1.42E-03		
619	2.61E-02	660	1.35E-02	701	4.69E-03	742	1.38E-03		
620	2.59E-02	661	1.32E-02	702	4.55E-03	743	1.36E-03		
621	2.57E-02	662	1.30E-02	703	4.41E-03	744	1.31E-03		
622	2.55E-02	663	1.26E-02	704	4.28E-03	745	1.28E-03		
623	2.52E-02	664	1.24E-02	705	4.17E-03	746	1.23E-03		
624	2.50E-02	665	1.21E-02	706	4.04E-03	747	1.19E-03		
625	2.47E-02	666	1.18E-02	707	3.93E-03	748	1.16E-03		

3.0 Results - Goniometric Measurements

Test conditions

Goniometer distance (m)	1
Temperature (°C)	25±1
Stabilization time (min)	50



Instrument

	Instrument	Manufacture	Model	
Photometric	Photometer and color meter	Minolta	CL-200A	
Electrical instrument	Power supply for test lamps	APT	Variplus 105	
	Power meter for test lamps	Chroma	66202	
Thermometer	Digital multimeter	YOKOGAWA	TY720	

Measurement results

Photometric		Electrical		
Central beam candle power(cd)	7511	Input voltage (V)	119.6	
Beam Angle (°)	23	Current (A)	0.156	
Field Angle (°)	39	Power (W)	18.4900	
Chromaticity coordinates	u'= 0.2515	pf	0.9890	
	v'= 0.5205			
	x = 0.4369			
	y = 0.4019			
CCT (K)	3000			

Luminous intensity distribution




Zonal Lumen Tabulation					
Zones (°)	Lumens	%lamp	Zones (°)	Lumens	%lamp
0-5	69.1	11.6%	45-50	7.6	1.3%
5-10	165.3	27.8%	50-55	6.5	1.1%
10-15	164.6	27.7%	55-60	5.8	1.0%
15-20	95.2	16.0%	60-65	4.8	0.8%
20-25	30.2	5.1%	65-70	4.2	0.7%
25-30	9.2	1.6%	70-75	3.2	0.5%
30-35	8.7	1.5%	75-80	1.9	0.3%
35-40	8.8	1.5%	80-85	1.2	0.2%
40-45	7.9	1.3%	85-90	0.8	0.1%
Total lumen					595

Accumulated Zonal Lumen Tabulation					
Zones (°)	Lumens	%lamp	Zones (°)	Lumens	%lamp
0-5	69.1	11.6%	0-50	566.5	95.2%
0-10	234.4	39.4%	0-55	573.0	96.3%
0-15	399.0	67.1%	0-60	578.8	97.3%
0-20	494.1	83.1%	0-65	583.6	98.1%
0-25	524.4	88.2%	0-70	587.8	98.8%
0-30	533.6	89.7%	0-75	591.0	99.4%
0-35	542.3	91.2%	0-80	592.9	99.7%
0-40	551.1	92.6%	0-85	594.0	99.9%
0-45	559.0	94.0%	0-90	594.8	100.0%

Center and edge illuminance, beam and field diameter

Distance (m)	E on axis (lx)	Beam D(m)	E on the edge of beam (lx)	Field D(m)	E on the edge of field (lx)
1.0	3657	0.33	1758	0.7	308
1.5	1626	0.49	781	1.0	137
2.0	914	0.65	440	1.4	77
2.5	585	0.81	281	1.7	49
3.0	406	0.98	195	2.1	34
3.5	299	1.14	144	2.4	25
4.0	229	1.30	110	2.8	19
4.5	181	1.47	87	3.1	15
5.0	146	1.63	70	3.5	12
5.5	121	1.79	58	3.8	10
6.0	102	1.95	49	4.2	9
6.5	87	2.12	42	4.5	7
7.0	75	2.28	36	4.9	6
7.5	65	2.44	31	5.2	5
8.0	57	2.61	27	5.6	5
8.5	51	2.77	24	5.9	4
9.0	45	2.93	22	6.3	4
9.5	41	3.09	19	6.6	3
10.0	37	3.26	18	7.0	3

Beam illuminance vs. distance



Luminous Intensity Distribution

Angle (°C)	CP (cd)	Angle (°C)	CP (cd)	Angle (°C)	CP (cd)	Angle (°C)	CP (cd)	Angle (°C)	CP (cd)
-90.0	4.5	-69.5	23.7	-49.0	46.6	-28.5	78.3	-8.0	4931.8
-89.5	4.6	-69.0	24.6	-48.5	48.1	-28.0	79.4	-7.5	5162.2
-89.0	4.7	-68.5	25.5	-48.0	49.8	-27.5	80.5	-7.0	5388.8
-88.5	4.9	-68.0	26.5	-47.5	51.2	-27.0	83.1	-6.5	5605.1
-88.0	5.0	-67.5	27.4	-47.0	52.1	-26.5	88.1	-6.0	5815.0
-87.5	5.1	-67.0	28.4	-46.5	52.6	-26.0	95.6	-5.5	6017.2
-87.0	5.4	-66.5	29.1	-46.0	53.0	-25.5	106.1	-5.0	6210.5
-86.5	5.8	-66.0	29.6	-45.5	53.5	-25.0	120.3	-4.5	6392.3
-86.0	6.1	-65.5	29.6	-45.0	53.9	-24.5	137.9	-4.0	6568.9
-85.5	6.4	-65.0	29.2	-44.5	54.0	-24.0	159.6	-3.5	6736.6
-85.0	6.8	-64.5	28.9	-44.0	53.9	-23.5	185.7	-3.0	6891.5
-84.5	7.2	-64.0	28.9	-43.5	53.5	-23.0	216.8	-2.5	7034.8
-84.0	7.6	-63.5	29.1	-43.0	53.5	-22.5	252.5	-2.0	7164.1
-83.5	7.8	-63.0	29.3	-42.5	53.5	-22.0	294.8	-1.5	7274.2
-83.0	8.2	-62.5	29.6	-42.0	53.8	-21.5	341.1	-1.0	7367.6
-82.5	8.4	-62.0	30.1	-41.5	54.3	-21.0	399.5	-0.5	7435.5
-82.0	8.8	-61.5	30.7	-41.0	55.2	-20.5	467.3	0.0	7484.1
-81.5	9.2	-61.0	31.2	-40.5	56.4	-20.0	549.1	0.5	7508.4
-81.0	9.5	-60.5	31.7	-40.0	58.5	-19.5	642.6	1.0	7511.0
-80.5	9.9	-60.0	32.3	-39.5	61.1	-19.0	747.6	1.5	7494.4
-80.0	10.1	-59.5	32.9	-39.0	63.1	-18.5	861.9	2.0	7461.1
-79.5	10.5	-59.0	33.7	-38.5	64.3	-18.0	985.9	2.5	7409.9
-79.0	10.9	-58.5	34.6	-38.0	65.0	-17.5	1118.1	3.0	7338.2
-78.5	11.3	-58.0	35.3	-37.5	65.7	-17.0	1265.9	3.5	7242.2
-78.0	11.6	-57.5	35.8	-37.0	66.2	-16.5	1423.4	4.0	7125.7
-77.5	12.0	-57.0	36.4	-36.5	66.9	-16.0	1587.2	4.5	6990.0
-77.0	12.5	-56.5	37.0	-36.0	68.1	-15.5	1762.6	5.0	6836.4
-76.5	13.2	-56.0	37.6	-35.5	69.6	-15.0	1944.3	5.5	6676.4
-76.0	13.7	-55.5	38.3	-35.0	71.2	-14.5	2129.9	6.0	6512.6
-75.5	14.2	-55.0	38.9	-34.5	72.2	-14.0	2323.2	6.5	6329.6
-75.0	14.8	-54.5	39.6	-34.0	73.2	-13.5	2520.3	7.0	6135.0
-74.5	15.5	-54.0	40.1	-33.5	74.2	-13.0	2725.1	7.5	5927.6
-74.0	16.1	-53.5	40.4	-33.0	74.9	-12.5	2932.5	8.0	5710.0
-73.5	16.8	-53.0	40.7	-32.5	74.8	-12.0	3143.7	8.5	5486.1
-73.0	17.4	-52.5	41.2	-32.0	74.8	-11.5	3352.3	9.0	5253.1
-72.5	18.0	-52.0	41.6	-31.5	74.8	-11.0	3573.7	9.5	5013.7
-72.0	18.9	-51.5	42.1	-31.0	74.5	-10.5	3797.7	10.0	4766.7
-71.5	19.8	-51.0	42.8	-30.5	74.4	-10.0	4023.0	10.5	4518.4
-71.0	20.7	-50.5	43.4	-30.0	74.9	-9.5	4250.9	11.0	4272.6
-70.5	21.8	-50.0	44.2	-29.5	75.8	-9.0	4476.1	11.5	4029.4
-70.0	22.8	-49.5	45.2	-29.0	77.1	-8.5	4702.7	12.0	3791.3

Luminous Intensity Distribution

Angle (°C)	CP (cd)	Angle (°C)	CP (cd)	Angle (°C)	CP (cd)	Angle (°C)	CP (cd)		
12.5	3558.4	33.0	75.1	53.5	36.4	74.0	13.3		
13.0	3325.4	33.5	74.9	54.0	35.6	74.5	12.7		
13.5	3093.7	34.0	74.5	54.5	34.9	75.0	11.9		
14.0	2865.9	34.5	74.4	55.0	34.3	75.5	11.4		
14.5	2643.2	35.0	73.6	55.5	33.8	76.0	10.9		
15.0	2429.4	35.5	71.8	56.0	33.3	76.5	10.2		
15.5	2228.5	36.0	70.0	56.5	33.0	77.0	9.6		
16.0	2032.6	36.5	69.0	57.0	32.8	77.5	9.1		
16.5	1843.2	37.0	68.4	57.5	32.3	78.0	8.4		
17.0	1658.9	37.5	67.3	58.0	31.5	78.5	7.9		
17.5	1481.0	38.0	66.0	58.5	30.7	79.0	7.4		
18.0	1312.0	38.5	64.8	59.0	30.1	79.5	7.0		
18.5	1152.0	39.0	63.9	59.5	29.4	80.0	6.7		
19.0	1004.3	39.5	63.1	60.0	28.9	80.5	6.4		
19.5	873.5	40.0	62.3	60.5	28.4	81.0	6.3		
20.0	760.2	40.5	61.3	61.0	27.5	81.5	6.0		
20.5	662.7	41.0	59.8	61.5	26.8	82.0	5.8		
21.0	577.4	41.5	58.0	62.0	26.0	82.5	5.6		
21.5	501.8	42.0	56.1	62.5	25.2	83.0	5.4		
22.0	433.4	42.5	54.7	63.0	24.4	83.5	5.2		
22.5	369.5	43.0	53.6	63.5	23.8	84.0	5.0		
23.0	313.0	43.5	52.7	64.0	23.0	84.5	4.9		
23.5	266.5	44.0	52.1	64.5	22.4	85.0	4.6		
24.0	227.8	44.5	51.3	65.0	21.9	85.5	4.5		
24.5	195.3	45.0	50.6	65.5	21.5	86.0	4.2		
25.0	168.2	45.5	49.8	66.0	21.4	86.5	4.0		
25.5	145.8	46.0	49.3	66.5	21.4	87.0	3.8		
26.0	127.6	46.5	48.8	67.0	21.2	87.5	3.6		
26.5	113.0	47.0	48.5	67.5	21.1	88.0	3.5		
27.0	101.8	47.5	48.1	68.0	20.9	88.5	3.2		
27.5	93.6	48.0	47.4	68.5	20.4	89.0	3.1		
28.0	88.2	48.5	46.3	69.0	20.0	89.5	2.9		
28.5	84.7	49.0	45.3	69.5	19.5	90.0	2.9		
29.0	82.4	49.5	44.2	70.0	18.9				
29.5	80.6	50.0	43.0	70.5	18.3				
30.0	79.7	50.5	41.9	71.0	17.8				
30.5	79.5	51.0	40.7	71.5	17.0				
31.0	78.7	51.5	39.7	72.0	16.4				
31.5	77.7	52.0	38.9	72.5	15.6				
32.0	76.8	52.5	38.1	73.0	14.8				
32.5	75.9	53.0	37.2	73.5	14.1				