



DuraMax® Reflector Flood

DuraMax 45W Med 120V R20 1CT

Philips DuraMax® Long Life Reflector Flood Bulbs reduce the hassle of replacing light bulbs every few months, since all DuraMax products last longer than standard incandescent light bulbs. Available in a variety of sizes and wattages. Use flood lights for general or ambient lighting; use spot lights to highlight artwork or architecture. Both are ideal for use in recessed cans or track lighting fixtures.

Product data

• General Characteristics

| | |
|--------------------|--------------------------------------|
| Base | Medium [Single Contact Medium Screw] |
| Base Information | Aluminum [Aluminum Base] |
| Bulb | R-20 |
| Bulb Finish | Frosted |
| Filament Shape | CC6 [Straight] |
| Operating Position | Universal [Any or Universal (U)] |
| Main Application | Household |
| Atmosphere | Gas |

• Light Technical Characteristics

| | |
|---------------|--------|
| Initial lumen | 385 Lm |
|---------------|--------|

• Electrical Characteristics

| | |
|---------|-------|
| Watts | 45 W |
| Voltage | 120 V |

• Product Dimensions

| | |
|------------------------------|---------------|
| Max Overall Length (MOL) - C | 3.94 (max) in |
|------------------------------|---------------|


• Product Data

| | |
|--------------------|------------------------------|
| Product number | 203232 |
| Full product name | DuraMax 45W Med 120V R20 1CT |
| Short product name | DuraMax 45W Med 120V R20 1CT |
| Pieces per Sku | 1 |
| eop_pck_cfg | 12 |
| Skus/Case | 12 |
| Bar code on pack | 46677203238 |
| Bar code on case | 50046677203233 |
| Logistics code(s) | 925154636304 |
| eop_net_weight_pp | 0.001 kg |

PHILIPS

sense and simplicity

Dimensional drawing



E26

E26, R20



© 2012 Koninklijke Philips Electronics N.V.
All rights reserved.

Specifications are subject to change without notice. Trademarks are the property of Koninklijke Philips Electronics N.V. or their respective owners.

www.philips.com/lighting

2012, February 1
data subject to change