

JC

- Only for Use in Approved Enclosed Halogen Fixtures
- Single Contact Bayonet Base - BA9s, BA15s
- Double Contact Bayonet Base - BA15d

- Universal Burn Position

Watts	Ushio Ordering Code	Ushio Lamp Description	Dimensions			Filament Type	Lumens lm	Color Temp K	Avg Life h	Bulb Finish	Case Qty
			Dia (A)	MOL (B)	LCL (C)						
Single Contact Bayonet Base – BA9s											
5	1000832	JC12V-5W/BA9S	0.35	1.10	0.59	C-2R	80	3000	240	Clear	10
10	1000810	JC12V-10W/BA9S	0.35	1.10	0.59	C-6	200	—	240	Clear	10
20	1000819	JC12V-20W/BA9S	0.35	1.18	0.53	C-6	340	2900	2000	Clear	10
Single Contact Bayonet Base – BA15s											
10	1003717	JC12V-10W/BA15S/XX	0.39	1.50	1.00	C-8	120	2850	10000	Clear	10
20	1003714	JC12V-20W/BA15S/XX	0.39	1.50	1.00	C-8	350	2900	10000	Clear	10
35	1003715	JC12V-35W/BA15S/XX	0.39	1.50	1.00	C-8	600	2900	8000	Clear	10
50	1003716	JC12V-50W/BA15S/XX	0.39	1.50	1.00	C-8	900	2950	8000	Clear	10
Double Contact Bayonet Base – BA15d											
35	1003754	JC12V-35W/BA15D	0.39	1.50	1.00	C-8	600	2900	10000	Clear	10
125	1000814	JC12V-125WB/BA15D*	0.59	1.92	1.13	C-8	1900	2800	1000	Clear	20

* Special Order Item

All dimensions shown in inches unless otherwise noted.

