

# Halogen FastFit

# Hi-Brite 7016G 1200W PG|X50 80V 1CT

Halogen FastFit lamps are replaced in seconds - thanks to the specially designed base. The compact filament ensures high beam intensity, while the shock-resistant design allows easy handling and reliable use in moving head systems. In addition, the highly innovative P3 technology allows use at higher temperatures, which further extends lifetime and consistency of light output. P3 technology also allows the lamp to be used in any burning position and enables more compact designs of fixtures. And because the FastFit design is also applied to Philips MSR/MSD Gold<sup>™</sup> lamps, switching lamp technologies is also quick and easy.

## Product data

#### • General Characteristics

Philips Code	7016G
ANSI Code	-
System Description	P3 Technology
Cap-Base	PGJX50
Bulb Finish	Clear
Filament Shape	Bi-Plane
Operating Position	any
Main Application	Entertainment
Life to 50% failures	200 hr

#### • Light Technical Characteristics

Color Temperature	3250 K
Technical	
Luminous Flux Lamp	36000 Lm

#### • Electrical Characteristics

Watts	1200 W
Voltage	80 V
Dimmable	Yes
Rapid Acting HBC	16 V
Fuse	

• Luminaire Design Requirements

**Pinch Temperature** 500 (max) C

### Dimensional drawing

#### • Product Dimensions

Overall Length C Diameter D Overall Width E Light Center Length Filament Dimensions (WxH) [mm] Filament Height H Filament Length W

#### • Product Data

Product number Full product name Short product name Pieces per Sku eop\_pck\_cfg Skus/Case Bar code on pack Bar code on case Logistics code(s) eop\_net\_weight\_pp

140 (max) mm 25 (max) mm 41 (max) mm 82 mm 12x10.5


10.5 mm 11.7 mm

201624 Hi-Brite 1200W FastFit Hi-Brite 1200W FastFit 1 10 10 8711500507075 8711500507082 924575228928 139.000 gr




# Halogen FastFit

# Dimensional drawing



#### Halogen FastFit

Ρ	roduct	C (Max)	D (Max)	E (Max)	H (Norm)	L (Norm)	W (Norm)
F	ii-Brite 7016G 1200W PGJX50 80V FastFit	140	25	41	10.5	82	11.7



PGJX50



 $\textcircled{\sc blue}$  2012 Koninklijke Philips Electronics N.V. All rights reserved.

Specifications are subject to change without notice. Trademarks are the property of Koninklijke Philips Electronics N.V. or their respective owners.

www.philips.com/lighting