



Products for Your Home

<input type="text"/>	SITE SEARCH	HOME	PRODUCTS	DESIGN WITH LIGHT	COUPONS / SPECIAL OFFERS
----------------------	-----------------------------	----------------------	--------------------------	-----------------------------------	--

[Where to Buy](#) | [FAQs](#) | [Contact Us](#)[Home](#) > [Products](#) > [Compact Fluorescent](#) > [Self-Ballasted](#), Biax® > 49885**49885 – FLE20TBX/2/SW/CD**

GE Soft White Biax® T4 - Facilities; Retail Display; Hospitality; Office; Restaurant

[Print](#)[Features & Photos](#)[Technical Specifications](#)[WHERE TO BUY](#)

**This product is no longer manufactured.
Remaining stock will be sold.**

[View Larger](#)**PRODUCT INFORMATION**

Base	Medium Screw (E26)
Product Code	49885
Description	FLE20TBX/2/SW/CD
UPC	043168498852

GENERAL CHARACTERISTICS

Lamp type	Compact Fluorescent - Self-Ballasted
Bulb	T4
Base	Medium Screw (E26)
ENERGY STAR® Qualified	Yes
Bulb Finish	Soft white
Equivalent Wattage	75 W
Rated Life	8000 hrs
Starting Temperature (MIN)	-15 °C (5 °F)
Total Harmonic Distortion (THD)	120 %
Primary Application	Standard; Facilities; Retail Display; Hospitality; Office; Restaurant

PHOTOMETRIC CHARACTERISTICS

Initial Lumens	1200
Mean Lumens	965
Nominal Initial Lumens per Watt	60
Color Temperature	2700 K

Color Rendering Index (CRI)	82
-----------------------------	----

ELECTRICAL CHARACTERISTICS

Wattage	20
Voltage	120
Input Voltage	120 V
Input Current	0.3050 A
Power Factor	0.6

DIMENSIONS

Maximum Overall Length (MOL)	6.9000 in (175.2 mm)
Nominal Length	6.900 in (175.2 mm)

 CAUTIONS & WARNINGS

[See list of cautions & warnings](#)

NOTES

Best performance if operated base up and at 77 degrees F (25C) ambient temperature.
Fluorescent lamp lumens decline during life
Lumens on one piece self ballasted lamp systems are measured base up.
Most one piece self ballasted lamps for incandescent sockets and plug-in lamps with screw-in adapters do not work with clip-on shades
Use only on 120V 60 Hz circuits. Do not use on dimming circuits, photocells or timers. Do not use in wet locations.

[Home](#) | [Products](#) | [Design with Light](#) | [Coupons / Special Offers](#) | [Where to Buy](#) | [FAQs](#) | [Contact Us](#)
[GE Around the World](#) | [Site Map](#) | [Commercial Products & Solutions](#) | [Press Room](#) | [Corporate Careers](#) | [Investor Information](#) | [Privacy Policy](#) | [Accessibility Statement](#) | [Terms of Use](#)

Copyright 2011 General Electric Company

Sign up for our e-News