



Products for Your Home

 [SITE SEARCH](#)
[HOME](#)[PRODUCTS](#)[DESIGN WITH LIGHT](#)[COUPONS /
SPECIAL
OFFERS](#)[Where to Buy](#) | [FAQs](#) | [Contact Us](#)[Home](#) > [Products](#) > [Specialty](#) > [Airport, City & Emergency Building , ED18](#) > 26430**26430 – LU250/CP**

GE Lucalox® High Pressure Sodium ED18 - Street Lighting

[Print](#)[Features & Photos](#)[Technical Specifications](#)[WHERE TO BUY](#)[View Larger](#)**PRODUCT INFORMATION**

ANSI Code	S50
Base	Mogul Screw (E39)
Product Code	26430
Description	LU250/CP
UPC	043168264303

GENERAL CHARACTERISTICS

Lamp type	High Intensity Discharge - High Pressure Sodium
Bulb	ED18
Base	Mogul Screw (E39)
Bulb Finish	Clear
Wattage	250
Rated Life (MIN)	24000 hrs
Bulb Material	Hard glass
Lamp Enclosure Type (LET)	Open or enclosed fixtures
Primary Application	Street Lighting

PHOTOMETRIC CHARACTERISTICS

Initial Lumens	28000
Mean Lumens	25200
Nominal Initial Lumens per Watt	112
Color Temperature	2100 K
Color Rendering Index (CRI)	22
Effective Arc Length	2.640000 in (67.056000 mm)

ELECTRICAL CHARACTERISTICS

Burn Position	Universal burning position
Open Circuit Voltage (RMS lag ballast) (MIN)	198 V
Warm Up Time to 90% (MIN)	3 min
Warm Up Time to 90% (MAX)	4 min
Hot Restart Time to 90% (MAX)	1 min

DIMENSIONS

Maximum Overall Length (MOL)	9.7500 in (247.6 mm)
Nominal Length	9.750 in (247.6 mm)
Bulb Diameter (DIA)	2.250 in (57.1 mm)
Light Center Length (LCL)	5.750 in (146.0 mm)

CAUTIONS & WARNINGS

[See list of cautions & warnings](#)

Home | Products | Design with Light | Coupons / Special Offers | Where to Buy | FAQs | Contact Us
 GE Around the World | Site Map | Commercial Products & Solutions | Press Room | Corporate
 Careers | Investor Information | Privacy Policy | Accessibility Statement | Terms of Use

Copyright 2010 General Electric Company

Sign up for our e-Ne

Enter E-Mail Address