

brighten



The bright white radiance of the GE's LED retail PAR38 lamps is not just something you see, it's something you feel.

LED retail PAR38 lamps

For superior light in retail spaces, the 12 and 18-watt GE's LED retail PAR38 lamp offers the perfect blend of enhanced color quality, advanced optics, and reduced glare.

LOW-COST OPERATION

- For example, using only 12 watts of energy, save over \$215 in energy costs over the rated life of a lamp versus a standard 90-watt halogen lamp based on \$0.11 per kWh
- Energy efficiency and long life mean fewer lamp replacements versus standard incandescent and halogen light sources
- Our LED PAR lamps have less heat, UV or infrared in the beam, which reduces the potential for fading of materials and décor, compared to halogen or incandescent lamps

EXCELLENT COLOR RENDERING

- Available with a CRI of 80 - 91

COLOR TEMPERATURE

- Halogen-like color
- Available in 2700K and 3000K



LONG LIFE

- Up to 25,000 hours rated life (L70)

BEAM PATTERNS

- Available in 15°, 25° and 40° beam patterns

ENVIRONMENTALLY CONSCIOUS

- These lamps are energy efficient, contain no lead or mercury, and are compliant with material restriction requirements of RoHS

GE QUALITY AND RELIABILITY

- 3-year limited warranty

Featuring GE's exclusive **Visual Comfort Lens™** for the perfect blend of enhanced color quality, advanced optics and low glare. Exclusive Visual Comfort Lens™ Optics create halogen-like light and contrast, with the energy and cost-efficient benefits of an LED lamp.

To learn more about saving money and energy, go to: gelighting.com/ThinkLED

When you Think LED lighting, Think GE.

ecomaginationSM




imagination at work

Information provided is subject to change without notice. Please verify all details with GE. All values are design or typical values when measured under laboratory conditions, and GE makes no warranty or guarantee, expressed or implied, that such performance will be obtained under end-use conditions.

LED retail PAR38 lamps

Directional Lamps (PAR)

Bulb Shape	Base Type	Order Watts	Order Code	Description	Volts	Case Qty**	MOL (In)	Lumens Initial	CBCP	Initial Color Temp	CRI	Wattage Equivalent	*Rated Life L70 (Hrs)	Dimmable	ENERGY STAR® Status	#Location Rating	Additional Information			
PAR38 - Low Glare - Visual Comfort Lens™																				
	MED	12	63228	LED12DP38W830/15	120	6	5.32	1000	13500	3000	80	90W	25,000	Yes	★	Dry	Spot, 15° beam, White			
			63233	LED12DP38W830/25	120	6	5.32	1000	4800	3000	80	90W	25,000	Yes	★	Dry	Narrow Flood, 25° beam, White			
			63235	LED12DP38W830/40	120	6	5.32	1000	1900	3000	80	90W	25,000	Yes	★	Dry	Flood, 40° beam, White			
			63239	LED12DP38W827/15	120	6	5.32	960	12800	2700	80	90W	25,000	Yes	★	Dry	Spot, 15° beam, White			
			63323	LED12DP38W827/25	120	6	5.32	960	4600	2700	80	90W	25,000	Yes	★	Dry	Narrow Flood, 25° beam, White			
			63329	LED12DP38W827/40	120	6	5.32	960	1800	2700	80	90W	25,000	Yes	★	Dry	Flood, 40° beam, White			
			63330	LED12DP38W930/15	120	6	5.32	860	11400	3000	91	90W	25,000	Yes	★	Dry	Spot, 15° beam, White			
			63331	LED12DP38W930/25	120	6	5.32	860	4100	3000	91	90W	25,000	Yes	★	Dry	Narrow Flood, 25° beam, White			
			63332	LED12DP38W930/40	120	6	5.32	860	1600	3000	91	90W	25,000	Yes	★	Dry	Flood, 40° beam, White			
			63333	LED12DP38W927/15	120	6	5.32	820	11000	2700	91	90W	25,000	Yes	★	Dry	Spot, 15° beam, White			
			63334	LED12DP38W927/25	120	6	5.32	820	3900	2700	91	90W	25,000	Yes	★	Dry	Narrow Flood, 25° beam, White			
			63343	LED12DP38W927/40	120	6	5.32	820	1550	2700	91	90W	25,000	Yes	★	Dry	Flood, 40° beam, White			
				18	18	94909	LED18D38W830/15	120	6	5.31	1400	8700	3000	80	85W	25,000	Yes	★	Dry	Spot, 15° beam, White
						94549	LED18D38W830/25	120	6	5.31	1400	5100	3000	80	100W	25,000	Yes	★	Dry	Narrow Flood, 25° beam, White
94910	LED18D38W830/40	120				6	5.31	1400	2800	3000	80	120W	25,000	Yes	★	Dry	Flood, 40° beam, White			
94903	LED18D38W930/15	120				6	5.31	1200	7500	3000	91	75W	25,000	Yes	★	Dry	Spot, 15° beam, White			
94904	LED18D38W930/25	120				6	5.31	1200	4400	3000	91	100W	25,000	Yes	★	Dry	Narrow Flood, 25° beam, White			
94905	LED18D38W930/40	120				6	5.31	1200	2400	3000	91	120W	25,000	Yes	★	Dry	Flood, 40° beam, White			
94901	LED18D38W927/15	120				6	5.31	1100	7100	2700	91	75W	25,000	Yes	★	Dry	Spot, 15° beam, White			
94198	LED18D38W927/25	120				6	5.31	1100	4100	2700	91	95W	25,000	Yes	★	Dry	Narrow Flood, 25° beam, White			
94902	LED18D38W927/40	120	6	5.31	1100	2300	2700	91	120W	25,000	Yes	★	Dry	Flood, 40° beam, White						

Get more information at
GELighting.com/ThinkLED

Information provided is subject to change without notice. Please verify all details with GE. All values are design or typical values when measured under laboratory conditions, and GE makes no warranty or guarantee, expressed or implied, that such performance will be obtained under end-use conditions.

* The life rating is based on the hours of operation the lamp will provide before reaching 70% of its original rating (L70)

** Minimum order quantity = 6

★ ENERGY STAR® status. Certified as meeting ENERGY STAR® guidelines.

UL 1993 Environmental Requirements for LED LAMPS

Location, damp - Exterior or interior location that is normally or periodically subject to condensation of moisture in, on, or adjacent to, electrical equipment, and includes partially protected locations.

Location, dry - Location not normally subject to dampness, may include a location subject to temporary dampness, i.e., building under construction, provided ventilation is adequate to prevent an accumulation of moisture.

Location, wet - Location in which water or other liquid can drip, splash, or flow on or against electrical equipment.

^ Incondescent or Halogen wattage equivalencies based on ENERGY STAR® guidelines using lumens or CBCP according to lamp type

Notes: 1) Product descriptions ending in "7TP" indicate a carded blister or clamshell package nested in a tray for shelf display. Cards also designed for hook display.

2) LED A19 Locking device works on PC: 85791, 85792, 89898, 62182, 89899 and 89900



Product is compliant with material restriction requirements of RoHS

ENERGY STAR® and the ENERGY STAR® logo are registered U.S. marks

ecomaginationSM



www.gelighting.com

GE and the GE Monogram are trademarks of the General Electric Company. All other trademarks are the property of their respective owners. Information provided is subject to change without notice. All values are design or typical values when measured under laboratory conditions. GE Lighting and GE Lighting Solutions, LLC are businesses of the General Electric Company. © 2014 GE.

63554 (Rev 8/26/14)