

illuminate



The bright white radiance of GE's LED A-Line lamps is not just something you see, it's something you feel.

LED A-Line general purpose lamps

GE offers dimmable LED A-Line lamps as excellent replacements for standard 40-watt, 60-watt, 75-watt and 100-watt incandescent lamps.

LOW-COST OPERATION

- For example, a 60-watt incandescent replacement lamp using 13 watts of energy and producing 800 lumens can save over \$129 in energy costs over the rated life of the lamp versus a standard 840 lumen, 60-watt incandescent A19 based on \$0.11 per kWh
- Energy efficiency and long life mean fewer lamp replacements versus standard incandescent or halogen light sources

EXCELLENT COLOR RENDERING

- Available with a CRI of 78 - 90

COLOR TEMPERATURE

- Halogen-like color
- Available in 2700K, 2900K and 3000K

LONG LIFE

- Up to 50,000 hours rated life (L70)

DIMMABLE

- Dims from 100% to as low as 10%

ENVIRONMENTALLY CONSCIOUS

- These lamps are energy efficient, contain no lead or mercury, and are compliant with material restriction requirements of RoHS

GE QUALITY AND RELIABILITY

- 3-year limited warranty

To learn more about saving money and energy, go to: gelighting.com/ThinkLED

When you Think LED lighting, Think GE.

ecomaginationSM








imagination at work

Information provided is subject to change without notice. Please verify all details with GE. All values are design or typical values when measured under laboratory conditions, and GE makes no warranty or guarantee, expressed or implied, that such performance will be obtained under end-use conditions.

LED A-Line general purpose lamps

A-Line Lamps

Bulb Shape	Base Type	Watts	Order Code	Description	Volts	Case Qty**	MOL (In)	Lumens Initial	CBCP	Initial Color Temp	CRI	Wattage Equivalent	*Rated Life L70 (Hrs)	Dimmable	ENERGY STAR® Status	#Location Rating	Additional Information	
A-15																		
	MED	1	76461	LED1A15G/TP	120	3	3.5					-	12,000	-			Dry	Green
		2.5	78655	LED2A15W	120	48**	3.5	80	2900	82	-	12,000	-	-			Dry	White
			78656	LED2A15CLR	120	48**	3.5	80	2900	82	-	12,000	-	-			Dry	Clear
	3	63011	LED3A15/W/TP	120	3	3.5	120	3000	80	-	15,000	-	-			Dry	White	
		63012	LED3A15/C/TP	120	3	3.5	120	3000	80	-	15,000	-	-			Dry	Clear	
		MED	4.5	68173	LED4DA15-W/TP	120	3.5	4.43	270	2700	82	25W	15,000	Yes			Damp	White
			68174	LED4DA15-C/TP	120	3.5	4.43	270	2700	82	25W	15,000	Yes			Damp	Clear	
			89987	LED4.5DA15-C/TP	120	3	3.5	300	2700	80	40W	15,000	Yes			Damp	Clear	
A-19																		
	MED	7	89984	LED7DA19V2/827W	120	6	4.43	470	2700	80	40W	25,000	Yes			Damp	White, Semi-Omni	
			14063	LED7DAV3/827W	120	6	4.63	470	2700	80	40W	25,000	Yes			Damp	White, Semi-Omni	
			95928	LED7DAV3/5K	120	6	4.63	500	5000	80	40W	25,000	Yes			Damp	White, Semi-Omni	
			11332	LED7DA19/827	120	6	4.43	450	2700	80	40W	25,000	Yes			Damp	White, Omnidirectional	
	8	85792	LED8DA19/827	120	6	4.43	450	2700	80	40W	25,000	Yes	★		Dry	White, Omnidirectional		
		9	65385	LED9DA19/830	120	6	4.43	450	3000	82	40W	50,000	Yes	★		Dry	White, Omnidirectional	
	11	89983	LED11DA19V2/827W	120	6	4.43	800	2700	80	60W	15,000	Yes			Damp	White, Semi-Omni		
			11328	LED11DA19/827	120	6	4.43	800	2700	80	60W	25,000	Yes	★		Damp	White, Omnidirectional	
				13791	LED11DAV3/827W	120	6	4.63	800	2700	78	60W	25,000	Yes			Damp	White, Semi-Omni
				13791	LED11DAV3/827W	120	6	4.63	800	2700	78	60W	25,000	Yes	★		Damp	White, Semi-Omni
		13	85791	LED13DA192/827	120	6	4.43	800	2700	80	60W	25,000	Yes	★		Dry	White, Omnidirectional	
A-Line Reveal																		
	MED	8	69220	LED8DA19RVL/TP	120	3	4.43	360	2700	90	40W	25,000	Yes			Damp	White, Semi-Omni	
		11	69204	LED11DA19RVL/TP	120	3	4.43	570	2700	90	60W	15,000	Yes			Damp	White, Semi-Omni	
A-21																		
	MED	14	94936	LED14DA21/827W	120	6	5.28	1100	2700	80	75W	15,000	Yes			Damp	White, Semi-Omni	
		16	14074	LED16DA21/827	120	6	5.28	1600	2700	80	100W	25,000	Yes	★		Damp	White, Omnidirectional	
Locking Device																		
			62182	LED A19 LOCK DEV ²														White, Kit

Get more information at GELighting.com/ThinkLED

Information provided is subject to change without notice. Please verify all details with GE. All values are design or typical values when measured under laboratory conditions, and GE makes no warranty or guarantee, expressed or implied, that such performance will be obtained under end-use conditions.

* The life rating is based on the hours of operation the lamp will provide before reaching 70% of its original rating (L70)

** Minimum order quantity = 6

★ ENERGY STAR® status. Certified as meeting ENERGY STAR® guidelines.

UL 1993 Environmental Requirements for LED LAMPS

Location, damp - Exterior or interior location that is normally or periodically subject to condensation of moisture in, on, or adjacent to, electrical equipment, and includes partially protected locations.

Location, dry - Location not normally subject to dampness, may include a location subject to temporary dampness, i.e., building under construction, provided ventilation is adequate to prevent an accumulation of moisture.

Location, wet - Location in which water or other liquid can drip, splash, or flow on or against electrical equipment.

^ Incandescent or Halogen wattage equivalencies based on ENERGY STAR® guidelines using lumens or CBCP according to lamp type

Notes: 1) Product descriptions ending in "7TP" indicate a carded blister or clamshell package nested in a tray for shelf display. Cards also designed for hook display.

2) LED A19 Locking device works on PC: 85791, 85792, 89898, 62182, 89899 and 89900



Product is compliant with material restriction requirements of RoHS

ENERGY STAR® and the ENERGY STAR® logo are registered U.S. marks

ecomaginationSM



www.gelighting.com

GE and the GE Monogram are trademarks of the General Electric Company. All other trademarks are the property of their respective owners. Information provided is subject to change without notice. All values are design or typical values when measured under laboratory conditions. GE Lighting and GE Lighting Solutions, LLC are businesses of the General Electric Company. © 2014 GE.

63563 (Rev 8/26/14)