

Use the Maestro Wireless family of products to build custom solutions for commercial spaces without spending a lot of time on the job.

- Lutron's reliable Clear Connect™ RF Technology is ideal for renovation as well as new construction.
- · Easily install a 3-way dimmer or an occupancy sensor without pulling new wire.
- Hassle-free set up of dimmer, switch, Pico™ wireless control, and occupancy sensor.
- · Build custom solutions for any commercial space, including conference rooms, restrooms, hotel rooms, storage areas, corridors, and more.





Maestro Wireless dimmer and Pico wireless control



lamp dimmer





clip



table stand



Radio Powr Savr_{TM} wireless occupancy/vacancy sensor





ordering information

commercial product offering

Model number	Control Type	Maximum Capacity
MRF2-10D-120-	single-pole/multi-location	120 V, 1000 W incandescent/
	spec grade dimmer	halogen, magnetic low voltage
MRF2-6ND-120-	single-pole/multi-location	120 V, 600 W incandescent/
	spec grade neutral wire dimmer	halogen, magnetic low voltage
MA-R-	multi-location	120 V, provides multi-location dimming
	companion dimmer	for additional locations
MRF2-8S-DV-	single-pole/multi-location spec grade non-neutral switch	120V/277V, 8 A light, incandescent, halogen,
		MLV, ELV, non-dim fluorescent ballasts,
		does not require a neutral wire connection
MRF2-8ANS-120-	single-pole/multi-location spec grade switch	120 V, 8 A light or 5.8 A fan, incandescent,
		halogen, MLV, ELV, non-dim fluorescent ballasts,
		and general purpose fans
MA-AS-	multi-location	120 V, provides multi-location switching
	companion switch	for up to nine additional locations
MRF2-6ANS-277-	single-pole/multi-location	277 V, 6 A light, MLV, ELV,
	spec grade switch	non-dim fluorescent ballasts
MA-AS-277-	multi-location	277 V, provides multi-location switching
	companion switch	for up to nine additional locations
MRF2-3LD-	plug-in lamp dimmer	300 W, inc./halogen for table or floor lamps
Pico™ wireless con	ntrol and accessories	
MRF2-3BRL-L-	Pico wireless control – communicates wirelessly with up to 10 Maestro Wireless	
	dimmers, lamp dimmers, and switches	
QSA-PED1-	table stand for Pico wireless control	
CW	Claro _® wallplate in 1-4 openings	
Radio Powr Savr™	wireless occupancy and vacancy sen	sor _
LRF2-OCRB-P-WH	occupancy and vacancy sensor – auto-on/auto-off or manual on/auto-off	
LRF2-VCRB-P-WH	vacancy sensor – manual on/auto-off only (complies with CA Title 24 requirements)	

Products available in the following colors:

sensors - white (WH) only

lamp dimmers & table stands (for Pico wireless control) - white (WH), black (BL)

Pico wireless controls:

gloss finish – white and gray (WG), white (WH), ivory (IV), almond (AL),

light almond (LA), gray (GR), brown (BR), black (BL)

dimmers, switches and Claro wallplates:

gloss finish – white (WH), ivory (IV), almond (AL), light almond (LA), gray (GR), brown (BR), black (BL)

satin finish – hot (HT), merlot (MR), plum (PL), turquoise (TQ), sea glass (SG), taupe (TP), eggshell (ES),

biscuit (BI), snow (SW), palladium (PD), midnight (MN), sienna (SI), terracotta (TC), greenbriar (GB), bluestone (BG), mocha stone (MS), goldstone (GS), desert stone (DS),

stone (ST), limestone (LS)



Customer Service 1.888.LUTRON1
Technical Support Center 24/7 1.800.523.9466

