2.94" (75mm)

4.69" (119mm)

Shown actual size: Skylark® preset dimmer and 1-gang Claro® wallplate in almond (AL)

SKYLARK® dimmers

product family features
- rocker switch returns light to your favorite light level
- slide up to brighten, down to dim (adjust light to suit any activity)
- coordinating Claro® wallplates available separately (including stainless steel)
- eco-dim® model available

available models

source type
- incandescent/halogen lighting
- magnetic low-voltage lighting
- electronic low-voltage lighting
- fluorescent lighting
- LED lighting
- dimmable compact fluorescent
- quiet 3-speed fan controls
- quiet 3-speed fan/light controls
- fully variable fan controls

control locations

available colors (see page 12 for color swatches)

colors (gloss finish)

WH	white		**GR**	gray
IV	ivory		**BR**	brown
AL	almond		**BL**	black
LA	light almond			

dimmers with on/off switch

- rocker switch turns on/off
- slide up to brighten, down to dim
- eco-dim® model guarantees at least 15% energy savings compared to a standard switch

incandescent/halogen

single pole	600 W	**S-600P-**
single pole	1000 W	**S-10P-**
3-way	600 W	**S-603P-**
3-way	1000 W	**S-103P-**

incandescent/halogen — eco-dim®†   NEW

single pole/3-way	600 W	**S-603PG-**

magnetic low-voltage

single pole	600 VA (450 W)	**SLV-600P-**
3-way	600 VA (450 W)	**SLV-603P-**

Suggested maximum lighting load for magnetic low-voltage dimming is 450 W for 600 VA products to allow for transformer losses.

electronic low-voltage*

single pole	300 W	**SELV-300P-**
3-way	300 W	**SELV-303P-**

requires neutral wire connection

† available in white, ivory, almond, and light almond

dimmers with on/off switch & locator light

- rocker switch turns on/off
- slide up to brighten, down to dim
- includes locator light

incandescent/halogen

single pole	600 W	**S-600PNL-**
single pole	1000 W	**S-10PNL-**
3-way	600 W	**S-603PNL-**
3-way	1000 W	**S-103PNL-**

slide-to-off dimmers

- slide up to on/brighten, down to dim/off

incandescent/halogen

single pole	600 W	**S-600-**
single pole	1000 W	**S-1000-**