

Dimmable CFL & LED bulbs

Compatible with Lutron 100W & 150W C-L® dimmers



This list is designed to help you select bulbs that are compatible with Lutron C·L dimmers. The CFL and LED bulbs on this list were extensively tested by Lutron; the Lutron C·L dimmers were evaluated by UL and meet applicable safety standards.

How to use this list

If you already have a bulb:

Use the “Find” tool in your browser or PDF viewer to search for the model number that’s printed on the bulb. Then choose a C·L dimmer that’s compatible with that bulb.

If you already have a C·L dimmer:

Use the table of contents to find the corresponding pages for that control, and then select a bulb from that list.

What does “compatible” mean?

Compatible means that the bulbs can be dimmed, although the bulb’s dimming performance may not match what you’re used to seeing when dimming an incandescent or halogen bulb. These bulbs have also been electrically tested to confirm that the control may be used up to its full rated CFL/LED load without affecting the life of the control.

Products on this list are considered compatible with the respective Lutron C·L dimmers. Depending on the quality of the bulb you select, compatible bulbs may still:

- have less dimming range than an incandescent or halogen bulb
- dim less smoothly than an incandescent or halogen bulb
- flicker or shimmer at certain light levels
- buzz

For more information

If you'd like more information regarding bulb performance and test results, including dimming range, other dimmer options, and performance, please visit www.lutron.com/ledtool.

Warranty on your Lutron 100W C•L dimmer or 150W C•L dimmer will be void if used with bulbs that are not on this Lutron compatible bulb list.

Please note: Bulb variations in lamp design and construction affect performance. Bulb manufacturers can modify their bulbs at any time, without notice to Lutron. This prevents Lutron from ensuring ongoing compatibility. For up-to-date specifications, performance, and/or any related recall information about the bulb, please visit the bulb manufacturer's website.

This document provides information from manufacturers who are not Lutron agents or affiliates. The listing of a manufacturer or the existence of any external link to another website does not suggest that Lutron is endorsing the linked company, its products and/or its services. Purchasers should ask appropriate questions and request references before buying any products and/or entering a contract with any party. The information contained in this document is intended for illustrative and comparative purposes only, and is subject to change at any time. Lutron does not warrant that (a) the list of manufacturers is all-inclusive; (b) the information is complete, up-to-date, accurate and/or error-free; (c) the products and Lutron controls listed will always be compatible; and (d) that the information provided will be a viable or appropriate solution for your project needs. You are entirely responsible for and assume all risk for the use of the information.

Dimmable CFL & LED bulbs

Compatible with C·L® dimmers



LED bulbs for Caséta Wireless in-wall dimmer

PD-6WCL

Maximum wattage controlled: 150W



Brand	Wattage	Model number	Description
Cree	9W	BA19-08050OMF-12DE26-1U100	A19, Daylight, 5000K, 800 Lumen, Medium base
	9.5W	BA19-08027OMF-12DE26-2U100	A19, Soft White, 2700K, 800 Lumen, Medium base
	9.5W	CR4-575L	4" Downlight, 2700K, Medium Base
	9.5W	CR6-575L	6" Downlight, 2700K, Medium Base
	9.5W	CR6-575L-GU24	6" Downlight, 2700K, GU24 Base
	13.5W	BA19-08027OMN-12DE26-1U100	A19, Soft White, 2700K, 800 Lumen, E26, 13.5W
	18W	BA21-16050OMF-12DE26-1U100	A21, 2700K, 1600 Lumen, E26, 18W
Ecosmart	8W	ECS 19 CW 120	A19, Cool White, 5000K
	8W	ECS 19 WW 120	A19, Warm White, 3000K
	8W	ECS 20 CW FL 50WE 120	PAR20, 5000K, 490 Lumen
	8W	ECS 20 WW FL 50WE 120	PAR20, 3000K, 450 Lumen
	9.5W	ECO4-575L	4" Downlight, 2700K, Medium Base
	9.5W	ECO4-575L-50K	4" Downlight, 5000K, Medium Base
	9.5W	ECO4-575L-50K-GU24	4" Downlight, 5000K, GU24 Base
	9.5W	ECO-575L	6" Downlight, 2700K, Medium Base
	9.5W	ECO-575L-50K-GU24	6" Downlight, 5000K, GU24 Base
	9.5W	ECO-575L-GU24	6" Downlight, 2700K, GU24 Base
	10W	ECS BR30 65WE WW 120 DG	BR30, Warm White, 3000K, 650 Lumen, E26
	10.5W	ECS 30 75WE XXX GB XX 120	PAR30, various color temperatures
	11.5W	ECS BR30 65WE CW 120	BR30, 5000K, Medium Base
	11.5W	ECS BR30 65WE W27 120	BR30, 2700K, 650 Lumen, Medium Base
	14W	ECS BR40 90WE CW 120 DG	BR40, Daylight, 5000K, 1050 Lumen, E26
	15W	ECS BR30 W27 FL 120	BR30, Soft White, 2700K
24W	ECS 38 V2 WW FL 120	PAR38, Warm White, 3000K	
Feit	4.5W	R14DM/LED	R14, Soft White, 2700K, 300 Lumen, E26, 40WE
	5W	MR16/GU10/DM/LED†	MR16, GU10 Base
	6.5W	BPMR16/GU10/DM/LED†	MR16, GU10 base
	6.5W	MR16/GU10/DM/LED†	MR16, GU10 base
	6.5W	R16DM/LED†	R16, Soft White, 2700K, 400 Lumen, E26, 40WE

† Requires a minimum of 2 lamps

Dimmable CFL & LED bulbs

Compatible with C·L[®] dimmers



LED bulbs for Caséta Wireless in-wall dimmer

PD-6WCL

Maximum wattage controlled: 150W



Brand	Wattage	Model number	Description
Feit	7.5W	PAR20DM/5K/LED [†]	PAR20, 5000K
	7.5W	PAR20DM/LED [†]	PAR20, 3000K
	8W	BPCER20/DM/LED	R20, 2700K, 450 Lumen, E26 Medium base (70mA smooth reflector version)
	13W	BPCEBR30LED	BR30
	13.5W	A19/OM800/5K/LED	A19, 5000K, Omni Directional
	13.5W	A19/OM800/LED	A19, 3000K, Omni Directional
	13.5W	BPCEA19/OM800/LED	A19, Omni Directional
	13.5W	BPCEA19/OM800/LED/CAN	A19, Omni Directional
	17W	BR40/DM/LED [†]	BR40, 2700K, 1065 Lumen
	20.5W	LEDR56/827	5" or 6" Downlight, 2700K, 1245 Lumen
GE	8W	LED8DA19/827	A19, 2700K, 450 Lumen, E26
	14W	LED14DA21V2/827W	A21, 2700K, 1100 Lumen, E26
Lighting Science	8W	DFN 19 CW 120	A19, Cool White, 5000K
	8W	DFN 19 NW 120	A19, Neutral White, 4000K
	8W	DFN 19 W27 120	A19, Warm White, 2700K
	8W	DFN 19 WW 120	A19, Warm White, 3000K
	10.5W	LS 30 75WE XXX GB XX 120	PAR30, various color temperatures
	11.5W	DFN BR30 65WE CW 120	BR30, Cool White, 5000K, Medium base
	11.5W	DFN BR30 65WE NW 120	BR30, Neutral White, 4000K, Medium base
	11.5W	DFN BR30 65WE W27 120	BR30, Warm White, 2700K, Medium base
	11.5W	DFN BR30 65WE WW 120	BR30, Warm White, 3000K, Medium base
	13W	LS GLP6 W27 120 WH S1 BX	6" Downlight, 2700K, E26 retrofit
	15W	DFN BR30 CW FL 120	BR30, Cool White, 5000K
	15W	DFN BR30 NW FL 120	BR30, Neutral White, 4000K
	15W	DFN BR30 W27 FL 120	BR30, Warm White, 2700K
	15W	DFN BR30 WW FL 120	BR30, Warm White, 3000K
	24W	DFN 38 CW V2 FL 120	PAR38, Cool White, 5000K
	24W	DFN 38 CW V2 NFL 120	PAR38, Cool White, 5000K
	24W	DFN 38 NW V2 FL 120	PAR38, Neutral White, 4000K
	24W	DFN 38 NW V2 NFL 120	PAR38, Neutral White, 4000K
	24W	DFN 38 W27 V2 FL 120	PAR38, Warm White, 2700K
	24W	DFN 38 W27 V2 NFL 120	PAR38, Warm White, 2700K

[†] Requires a minimum of 2 lamps

Dimmable CFL & LED bulbs

Compatible with C·L® dimmers



LED bulbs for Caséta Wireless in-wall dimmer

PD-6WCL

Maximum wattage controlled: 150W



Brand	Wattage	Model number	Description
Lighting Science	24W	DFN 38 WW V2 FL 120	PAR38, Warm White, 3000K
	24W	DFN 38 WW V2 NFL 120	PAR38, Warm White, 3000K
Lumapro	8W	8A19/LED/DIM/30	A19, Warm White, 3000K (6GEM2)
	8W	8A19/LED/DIM/50	A19, Cool White, 5000K (6GEM3)
Philips	4W	9290002120	MR16, Bright White, 3000K, 200 Lumen, GU10, 4W
	4.5W	9290002439	Candle, Warm White, 2700K, 320 Lumen, E26 base, Post Light
	7W	9290002706	A19 Slim Style, Daylight, 5000K, 450 Lumen, E26
	8W	9290002267	A19, 2700K, 478 Lumen
	8W	9290002295	A19, 5000K
	8.5W	9290002543	BR30, 5000K, 730 LUMEN, 8.5W
	10.5W	9290002544	BR30, 2700K, 730 LUMEN, 8.5W
	11W	9290002268	A19, 2700K, 830 Lumen
	11W	9290002296	A19, 5000K, 830 Lumen
	13W	9290002233	PAR30, 2700K, 784 Lumen
	13W	9290002234	PAR30, 2700K, 770 Lumen
	13W	9290002201	PAR30, 3000K, 804 Lumen
	13W	9290002323	PAR30
	13W	9290002523 13PAR38/F25 3000 DIM AF RO	PAR38, 3000K, 950 Lumen
	14.5W	9290002199	BR40, 2700K, 832 Lumen
	15W	9290002595	A21, Soft White, 2700K, 1180 Lumen, E26, 19W
	17W	9290002018†	A21, 2700K
	17W	17E26A21D†	A21, 2700K
	18W	9290002202	PAR38, 3000K, 951 Lumen, Medium Base
	18W	9290002236	PAR38
	18W	9290002237	PAR38
	18W	9290002245	PAR38, 2700K, 938 Lumen
	18W	9290002246	PAR38
	18W	9290002307	PAR38
	18W	9290002308	PAR38
	18W	9290002309	PAR38

† Requires a minimum of 2 lamps

Dimmable CFL & LED bulbs

Compatible with C·L[®] dimmers



LED bulbs for Caséta Wireless in-wall dimmer

PD-6WCL

Maximum wattage controlled: 150W



Brand	Wattage	Model number	Description
Philips	18W	9290002310	PAR38
	18W	9290002311	PAR38
	18W	18E26PAR38-3	PAR38
	18W	18E26PAR38-4	PAR38
Samsung	7W	STIPLW8300711AB	SI-P8V071AB0US
Satco	11W	S9084	PAR30, 3000k, 780 Lumen, E26, short neck, 25° Beam
	11W	S9085	PAR30, 4000K, 780 Lumen, E26, short neck, 25° Beam
	11W	S9086	PAR30, 3000k, 780 Lumen, E26, short neck, 40° Beam
	11W	S9087	PAR30, 4000K, 780 Lumen, E26, short neck, 40° Beam
	11W	S9088	PAR30, 3000K, 780 Lumen, E26, long neck, 25° Beam
	11W	S9089	PAR30, 4000K, 780 Lumen, E26, long neck, 25° Beam
	11W	S9090	PAR30, 3000K, 780 Lumen, E26, long neck, 40° Beam
	11W	S9091	PAR30, 4000K, 780 Lumen, E26, long neck, 40° Beam
	17W	S9092	PAR38, 3000K, 1200 Lumen, E26, 25° beam
	17W	S9093	PAR38, 4000K, 1200 Lumen, E26, 25° beam
	17W	S9094	PAR38, 3000K, 1200 Lumen, E26, 40° beam
	17W	S9095	PAR38, 4000K, 1200 Lumen, E26, 40° beam
	28W	LR38/15/27K/2000/xx	PAR38, 2700K, 2000 Lumen, E26
	28W	LR38/15/30K/2100/xx	PAR38, 3000K, 2100 Lumen, E26
	28W	LR38/25/27K/2000/xx	PAR38, 2700K, 2000 Lumen, E26
	28W	LR38/25/30K/2100/xx	PAR38, 3000K, 2100 Lumen, E26
28W	LR38/40/27K/2000/xx	PAR38, 2700K, 2000 Lumen, E26	
28W	LR38/40/30K/2100/xx	PAR38, 3000K, 2100 Lumen, E26	

Dimmable CFL & LED bulbs

Compatible with C·L® dimmers



LED bulbs for Caséta Wireless in-wall dimmer

PD-6WCL

Maximum wattage controlled: 150W



Brand	Wattage	Model number	Description
Solais	7W	LRP20/25/27K	PAR20, 2700K, 475 Lumen, E26, 25° Beam
	7W	LRP20/25/30K	PAR20, 3000K, 500 Lumen, E26, 25° Beam
	7W	LRP20/40/27K	PAR20, 2700K, 475 Lumen, E26, 40° Beam
	7W	LRP20/40/30K	PAR20, 3000K, 500 Lumen, E26, 40° Beam
	11W	LR20/25/27K/675/xx	PAR20, 2700K, 675 Lumen, E26, narrow flood
	11W	LR20/25/30K/750	PAR20, 3000K, 750 Lumen, E26, narrow flood
	11W	LR20/40/27K/675/xx	PAR20, 2700K, 675 Lumen, E26, wide flood
	11W	LR20/40/30K/750/xx	PAR20, 3000K, 750 Lumen, E26, wide flood
	16W	LR30/10/27K/1100/xx	PAR30, 2700K, 1100 Lumen, E26, short neck, 10° Beam
	16W	LR30/10/30K/1125/xx	PAR30, 3000K, 1125 Lumen, E26, short neck, 10° Beam
	16W	LR30/10/30K/1200/xx	PAR30, 3000K, 1200 Lumen, E26, short neck, 10° Beam
	16W	LR30/15/27K/1100/xx	PAR30, 2700K, 1100 Lumen, E26, short neck, 15° Beam
	16W	LR30/15/30K/1125/xx	PAR30, 3000K, 1125 Lumen, E26, short neck, 15° Beam
	16W	LR30/15/30K/1200/xx	PAR30, 3000K, 1200 Lumen, E26, short neck, 15° Beam
	16W	LR30/25/27K/1100/xx	PAR30, 2700K, 1100 Lumen, E26, short neck, 25° Beam
	16W	LR30/25/30K/1125/xx	PAR30, 3000K, 1125 Lumen, E26, short neck, 25° Beam
	16W	LR30/25/30K/1200/WH	PAR30, 3000K, 1200 Lumen, E26, short neck, 25° Beam
	16W	LR30/40/27K/1100/xx	PAR30, 2700K, 1100 Lumen, E26, short neck, 40° Beam
	16W	LR30/40/30K/1125/xx	PAR30, 3000K, 1125 Lumen, E26, short neck, 40° Beam
	16W	LR30/40/30K/1200/xx	PAR30, 3000K, 1200 Lumen, E26, short neck, 40° Beam
	16W	LRP38/25/27K	PAR38, 2700K, 1025 Lumen, E26, 25° Beam

Dimmable CFL & LED bulbs

Compatible with C·L® dimmers



LED bulbs for Caséta Wireless in-wall dimmer

PD-6WCL

Maximum wattage controlled: 150W



Brand	Wattage	Model number	Description
Solais	16W	LRP38/25/30K	PAR38, 3000K, 1100 Lumen, E26, 25° Beam
	16W	LRP38/40/27K	PAR38, 2700K, 1025 Lumen, E26, 40° Beam
	16W	LRP38/40/30K	PAR38, 3000K, 1100 Lumen, E26, 40° Beam
	20W	LR38/25/30K/1450/SL	PAR38, 3000K, 1450 Lumen, E26, 15° Beam
Sylvania	8W	LED8A/DIM/F/827	A19, 2700K
	8W	LED8A/DIM/F/830	A19, 3000K
	8W	LED8PAR16/DIM/930/FL36/P/LW	PAR16, Soft White, 390 Lumen
	8W	LED8PAR16/GU10/DIM/930/FL36/RP	PAR16, GU10, Soft White, 390 Lumen
	9W	LED/550/RT4/827/FL80/WRFL	4" Downlight, 2700K
	9W	LED/550/RT4/830/FL80/WRFL	4" Downlight, 3000K
	11W	LED11PAR20/DIM/930/FL30/P2	PAR20, Soft White, 550 Lumen
	12W	LED12BR30/DIM/HO/827	BR30, 2700K, Medium base
	12W	LED12BR30/DIM/HO/827/HVP	BR30, 2700K, Medium base
	17W	LED17PAR30LN/DIM/830/WSP15/P	PAR30, 3000K, 1200 Lumen, E26, spot
	17W	LED17PAR30LN/DIM/830/WSP20	PAR30, 3000K, 1200 Lumen, E26, wide spot
	17W	LED17PAR30LN/DIM/P/930/NFL25†	PAR30, 3000K, 900 Lumen
	20W	LED20PAR38/DIM/930/FL40/P2	PAR38
	21W	LED21/PAR38/DIM/P/930/FL30/HVP	PAR38, Warm White, 3000K, 1100 Lumen, E26, 21W
21W	LED21PAR38/DIM/P/930/FL30	PAR38, 3000K, 1100 Lumen	
Utilitech	3W	LG161/2DM/IF/LED†	G16.5, Warm White, 3000K, 200 Lumen, E12 base, frosted
	4.5W	LR14DMLED	R14, Soft White, 2700K, 300 Lumen, E26, 40WE
	4.8W	LA15DM/CL/300/LED†	A15, Warm White, 3000K, 300 Lumen, E26, clear
	4.8W	LA15DM/IF/300/LED†	A15, Warm White, 3000K, 300 Lumen, E26, frosted
	4.8W	LA15DMC/CL/300/LED†	A15, Warm White, 3000K, 300 Lumen, E12 base, clear
	4.8W	LCFCDM/300/LED†	Candle, Warm White, 3000K, 300 Lumen, E12 base, clear flame tip
	4.8W	LCFFDM/300/LED†	Candle, Warm White, 3000K, 300 Lumen, E12 base, frosted flame tip

† Requires a minimum of 2 lamps

Dimmable CFL & LED bulbs

Compatible with C·L® dimmers



LED bulbs for Caséta Wireless in-wall dimmer

PD-6WCL

Maximum wattage controlled: 150W



Brand	Wattage	Model number	Description
Utilitech	4.8W	LEFCDM/300/LED†	Candle, Warm White, 3000K, 300 Lumen, E26 base, clear flame tip
	4.8W	LG161/2DM/CL/300/LED†	G16.5, Warm White, 3000K, 300 Lumen, E12 base, clear
	4.8W	LG161/2DM/IF/300/LED†	G16.5, Warm White, 3000K, 300 Lumen, E12 base, frosted
	4.8W	LGMDM/CL/300/LED†	G16.5, Warm White, 3000K, 300 Lumen, E26, clear
	5W	LMR16GU10DM/LED†	MR16, GU10 Base
	6.5W	LMR16/GU10/DM/LED†	MR16, GU10 base
	6.5W	LMR16DMGU10†	MR16, GU10 base
	6.5W	LR16DMLED†	R16, Soft White, 2700K, 400 Lumen, E26, 40WE
	7.5W	LPAR20DM/5K/LED†	PAR20, 5000K
	7.5W	LPAR20DM/LED†	PAR20, 3000K
	8W	LR20DMLEDG2	R20, 2700K, 450 Lumen, E26 Medium base (70mA smooth reflector version)
	11W	DLS02-41127D1E-WF1	4" Downlight, Soft White, 2700K, 650 Lumen, E26 retrofit
	13W	DLS02-61327D1E-WF1	5" or 6" Downlight, Soft White, 2700K, 800 Lumen, E26 retrofit
	13W	DLS02-61350D1E-WF1	5" or 6" Downlight, Daylight, 5000K, 800 Lumen, E26 retrofit
	13W	LBR30DM/LEDG2	BR30
	13.5W	LA19/OM800/LED	A19, 3000K, 800 Lumen, Omni Directional
	16W	LBR40DMLEDG2†	BR40, 2700K, 1065 Lumen
	17W	BPCEBR40/DM/LED†	BR40
17W	LBR40DM/LED†	BR40, 2700K, 1065 Lumen	
Westinghouse	8W	8A19/LED/DIM/30	A19, Warm White, 3000K
	8W	8A19/LED/DIM/50	A19, Cool White, 5000K

† Requires a minimum of 2 lamps

Dimmable CFL & LED bulbs

Compatible with C·L® dimmers



CFL bulbs* for Caséta Wireless in-wall dimmer

PD-6WCL

Maximum wattage controlled: 150W



Brand	Wattage	Model	Description
GE	26W	FLE26HT3/2/DV/SW	Spiral
	14W	4R2014TD	R20, TruDim, 2700K
TCP	14W	4R2014TD30K	R20, TruDim, 3000K
	14W	4R2014TD35K	R20, TruDim, 3500K
	14W	4R2014TD41K	R20, TruDim, 4100K
	14W	4R2014TD50K	R20, TruDim, 5000K
	14W	4R2014TD65K	R20, TruDim, 6500K
	14W	4R2014TD65K	R20, TruDim, 6500K

* CFLs typically require a warmup period before their full dimming range is achieved.

Dimmable CFL & LED bulbs

Compatible with C·L® dimmers



LED bulbs for Caséta Wireless plug-in dimmer

PD-3PCL

Maximum wattage controlled: 100W



Brand	Wattage	Model number	Description
Cree	6W	BA19-04527OMF-12DE26-1U100	A19, Warm Soft White, 2700K, 450 Lumen, Medium base
	9W	BA19-08050OMF-12DE26-1U100	A19, Daylight, 5000K, 800 Lumen, Medium base
	9.5W	BA19-08027OMF-12DE26-2U100	A19, Soft White, 2700K, 800 Lumen, Medium base
	13.5W	BA19-08027OMN-12DE26-1U100	A19, Soft White, 2700K, 800 Lumen, E26, 13.5W
	18W	BA21-16050OMF-12DE26-1U100	A21, 2700K, 1600 Lumen, E26, 18W
Ecosmart	7W	ECS 25 40WE W27 120	G25, Warm White, 2700K
	8W	ECS 19 CW 120	A19, Cool White, 5000K
	8W	ECS 19 WW 120	A19, Warm White, 3000K
Feit	7.5W	PAR20DM/5K/LED†	PAR20, 5000K
	7.5W	PAR20DM/LED†	PAR20, 3000K
	9.5W	BPCER20/DM/LED	PAR20
	9.5W	PAR20/5K/LEDG5	PAR20, 5000K
	9.5W	PAR20/5K/LEDG5/CAN	PAR20, 5000K
	9.5W	PAR20/LEDG5	PAR20, 3000K, 450 Lumen
	9.5W	PAR20/LEDG5/CAN	PAR20
	10W	G25/DM/LED	G25, 3000K
	13.5W	A19/OM800/5K/LED	A19, 5000K, Omni Directional
	13.5W	A19/OM800/LED	A19, 3000K, Omni Directional
	13.5W	BPCEA19/OM800/LED	A19, Omni Directional
	13.5W	BPCEA19/OM800/LED/CAN	A19, Omni Directional
GE	18W	LED18D38W827/15	PAR38, 2700K, E26, 15° Beam
	18W	LED18D38W827/25	PAR38, 2700K, E26, 25° Beam
	18W	LED18D38W827/40	PAR38, 2700K, E26, 40° Beam
	18W	LED18D38W830/15	PAR38, 3000K, 1400 Lumen, E26, 15° Beam
	18W	LED18D38W830/25	PAR38, 3000K, 1400 Lumen, E26, 25° Beam
	18W	LED18D38W830/40	PAR38, 3000K, 1400 Lumen, E26, 40° Beam
	18W	LED18D38W927/15	PAR38, 2700K, 1100 Lumen, E26, 15° Beam
	18W	LED18D38W927/25	PAR38, 2700K, 1100 Lumen, E26, 25° Beam
	18W	LED18D38W927/40	PAR38, 2700K, 1100 Lumen, E26, 40° Beam
	18W	LED18D38W930/15	PAR38, 3000K, 1200 Lumen, E26, 15° Beam

Dimmable CFL & LED bulbs

Compatible with C·L® dimmers



LED bulbs for Caséta Wireless plug-in dimmer

PD-3PCL

Maximum wattage controlled: 100W



Brand	Wattage	Model number	Description
GE	18W	LED18D38W930/25	PAR38, 3000K, 1200 Lumen, E26, 25° Beam
	18W	LED18D38W930/40	PAR38, 3000K, 1200 Lumen, E26, 40° Beam
Lighting Science	8W	DFN 19 CW 120	A19, Cool White, 5000K
	8W	DFN 19 NW 120	A19, Neutral White, 4000K
	8W	DFN 19 W27 120	A19, Warm White, 2700K
	8W	DFN 19 WW 120	A19, Warm White, 3000K
Lumapro	8W	8A19/LED/DIM/30	A19, Warm White, 3000K (6GEM2)
	8W	8A19/LED/DIM/50	A19, Cool White, 5000K (6GEM3)
Philips	8W	9290002267	A19, 2700K, 478 Lumen
	8W	9290002295	A19, 5000K
	11W	9290002268	A19, 2700K, 830 Lumen
	11W	9290002296	A19, 5000K, 830 Lumen
	14.5W	9290002199	BR40, 2700K, 832 Lumen
	15W	9290002595	A21, Soft White, 2700K, 1180 Lumen, E26, 19W
	17W	9290002018	A21, 2700K
17W	17E26A21D	A21, 2700K	
Samsung	7W	STIPLW8300711AB	SI-P8V071ABOUS
Satco	10.5W	S9037	A19, 2700K, 810 Lumen, E26
	10.5W	S9038	A19, 3500K, 830 Lumen, E26
	10.5W	S9039	A19, 5000K, 870 Lumen, E26
Sylvania	8W	LED8A/DIM/F/827	A19, 2700K
	8W	LED8A/DIM/F/830	A19, 3000K
Utilitech	7.5W	LA19DM/LEDG2	A19, 3000K, 450 Lumen
	7.5W	LPAR20DM/5K/LED†	PAR20, 5000K
	7.5W	LPAR20DM/LED†	PAR20, 3000K
	9.5W	LPAR20/5K/LEDG5	PAR20, 5000K, 500 Lumen
	9.5W	LPAR20/LEDG5	PAR20, 3000K, 450 Lumen
	10W	LG25/DM/LED	G25, 3000K
	13.5W	LA19/OM800/LED	A19, 3000K, 800 Lumen, Omni Directional
Westinghouse	8W	8A19/LED/DIM/30	A19, Warm White, 3000K
	8W	8A19/LED/DIM/50	A19, Cool White, 5000K

† Requires a minimum of 2 lamps

Dimmable CFL & LED bulbs

Compatible with C·L® dimmers



CFL bulbs* for Caséta Wireless plug-in dimmer

PD-3PCL

Maximum wattage controlled: 100W



Brand	Wattage	Model	Description
GE	26W	FLE26HT3/2/DV/SW	Spiral

* CFLs typically require a warmup period before their full dimming range is achieved.