LUNERA SUSAN LAMP GEN 2 INSTALLATION GUIDE


Vertical Mount, E39/EX39 Mogul

Installation Instructions

 Power OFF the MH downlight fixture into which you will install the Susan Lamp. Wait for approximately 10 minutes before touching the existing MH bulb to allow it to cool off so it can be touched safely.

LUNERA[®]

- 2. Carefully remove the existing MH bulb. Unscrew the lamp from the base slowly to avoid breakage. Be sure to properly recycle the MH lamp.
- 3. Make sure the existing bulb wattage matches the Susan Lamp equivalent wattage. Check the lamp enclosure to ensure the Susan Lamp matches the lamp being replaced... i.e. Susan Lamp 400W/320W is replacing a 400W or 320W metal halide. If the Susan Lamp model does not match the rated fixture wattage, stop. Do not install.




- 4. Install the Susan Lamp into the existing E39/EX39 mogul socket. If the lamp does not seat properly, do not apply force. Check to make sure the fixture has the E39/EX39 mogul required socket.
- 5. Attach the Susan Lamp lanyard to the existing fixture. See diagram.
- 6. Turn ON power.

If the Susan Lamp flickers, strobes, or fails on installation, immediately Turn OFF power. The Susan Lamp may not be compatible with the intended installation.

LUNERA SUSAN LAMP GEN 2 INSTALLATION GUIDE Vertical Mount, E39/EX39 Mogul, E26 Medium




The Susan Lamp is designed to replace Metal Halide (MH) lamps in the following compatible applications.



Incompatible Applications

Installation of the Susan Lamp in **INCOMPATIBLE** MH applications may cause the Susan Lamp flicker, strobe, or fail entirely. If this is seen, please power down and immediately remove the lamp.



LUNERA®