

Traditional Re-inspired

LED Flush Mount Lighting on a whole new level

New generation, LED flush mount lighting solutions from Lithonia Lighting® excel in style, performance and value. From homes to hotels, restaurants to office spaces, these competitively-priced LED fixtures bring remarkable **energy savings** and inviting, **uniform illumination** to a wide range of residential and light commercial applications — **from a brand you trust.**

Benefits and Features

- Versatile style low-profile, transitional designs can mount to the wall or ceiling
- Dimmable down to 10% of output using standard triac dimmer
- Instant on AC-driven LED boards have zero inrush
- Easy-to-operate ability to put multiple fixtures on a single dimmer/circuit
- Installer-friendly compatible with all standard boxes; installation hardware is included
- Peace-of-mind long life output eliminates routine maintenance;












Easy to install and no lamps required, new LED lighting gives you as much as 50,000 hours of light and energy savings of up to 84%.*



Ordering Information

For shortest lead time, configure product using bolded options.							EXAMPLE: FMSATL 13 20840 BN			
Series	Size	Module/CRI		Color	Color Temperature		sh	Accessories		
FMSATL 13 FMSATL 16	LED flush mount 13" diameter LED flush mount 16" diameter	148 208	>80 >80	40 35 30	4000K 3500K ² 3000K	BN BZA	Brushed nickel Antique bronze	PKSATL BN PKSATL BZA	Pendant mounting kit, brushed nickel Pendant mounting kit, antique bronze	
FMDDHL 14	LED flush mount 14" diameter	208	>80	27	2700K ¹	BN BZA	Brushed nickel Antique bronze		nt, antique biolize	
FMDCGL 16	LED flush mount 17" diameter					BN BZ	Brushed nickel Bronze			
FMKMNL 14	LED flush mount 14" diameter					KR	Polished chrome			
FMCRNL 14	LED flush mount 14" diameter	208	>80	40	4000K1					
FMVELL 14	LED flush mount 14" diameter			35 30 27	3500K ² 3000K 2700K ¹					
FMMCL	LED closet light 8" diameter	8	>80	40	4000K					
FMLRL 11	11" LED low profile round flush mount	148	>80	40	4000K					
FMLRL 14	14" LED low profile round flush mount	208	>80	35	3500K ²					
FMLSL 11	11" LED low profile square flush mount	148	>80	30	3000K					
FMLSL 14	14" I FD low profile square flush mount	208	>80	27	2700K ²					

^{*}Cost based on 8hrs. of operation at 0.13 KWH.



² 90-day lead time for nonstandard color temperatures; minimum 50 order quantity.

³ Not dimmable





