

B11 5.5W DIM. TITANIUM LED SERIES



PRO



5.5W REPLACES



60W Inc.

80% Energy Savings

\$159 Savings per lamp*

- ⌚ Omnidirectional: 230° beam angle
- ⌚ High efficacy 91 LPW in Warm White
- ⌚ Available in E12 & E26 bases for various applications
- ⌚ Innovative crown lens creates unique sparkling effect
- ⌚ Energy efficient alternative to incandescent candle lighting
- ⌚ Smooth dimming with existing installations



25,000 H



DIMMABLE



EFFICACY



WARRANTY



CRI (Ra)



OMNI DIRECTIONAL



LM 79

LM 80

TM 21



SUITABLE FOR ALL DECORATIVE APPLICATIONS



B11 5.5W DIM. TITANIUM LED SERIES

APPLICATIONS

Chandelier



Sconce



Uplighting



Ref.# DS101-B11-5.5W

SPECIFICATIONS

| Product Model | 97823 5.5B11DIM/827 | 97824 5.5B11DIM/827/E26 |
|-----------------------------|------------------------|----------------------------|
| Type | B11 (candle) | B11 (candle) |
| Base | E12 | E26 |
| Power (W) | 5.5 | 5.5 |
| Voltage - Frequency | 120V 60Hz | 120V 60Hz |
| Color Temp. (ANSI) | Warm White 2700K | Warm White 2700K |
| CRI (Ra) | 80 | 80 |
| Typical lumens (lm) | 500 | 500 |
| Efficacy (LPW) | 91 | 91 |
| Beam Angle | 230° | 230° |
| Dimmable | Yes** | Yes** |
| Power Factor | 0.9 | 0.9 |
| Rated Lifetime - L70 (hrs.) | 25,000 | 25,000 |
| Dia. x MOL | 1.50"x4.21" (38x107mm) | 1.50"x4.16" (38x106mm) |
| Weight (lb. / g) | 0.11lb / 49g | 0.12lb / 54g |

* Savings per lamp based on \$0.11 / kw energy cost, 12 hrs / day lamp usage, \$2 incandescent with 1000-hr lifetime, \$16 LED with 25,000-hr lifetime

** List of tested dimmer switches available on website

*** Not intended for use in totally enclosed fixtures

**** Suitable for damp locations. Not for use where directly exposed to weather or water