

# PLL 17W DIR TITANIUM LED SERIES

Preliminary Specifications



PL:EDGE  
SERIES

17W REPLACES



40W  
CFL

60% Energy Savings

PRO



Support clip included

- Compatible with Instant Start & Programmed Start ballasts
- Easy to install - Plug & Play Direct
- Exceptional efficacy 124 LPW
- Suitable for use in totally enclosed fixtures
- Wide beam design: 280° light emitting area
- 0-10V dimming



50,000 H




BALLAST  
COMPATIBLE



PLUG  
&  
PLAY  
Direct



5  
YR  
WARRANTY



CRI (Ra)  
80



ENCLOSED\*



LM 79

LM 80

TM 21

IES



## EFFICIENCY AT WORK



# PLL 17W DIR TITANIUM LED SERIES

## Preliminary Specifications



### SPECIFICATIONS\*\*

Product Model	97745 17PLL/830/DIR	97746 17PLL/835/DIR	97747 17PLL/840/DIR
Type	PLL	PLL	PLL
Base	2G11	2G11	2G11
Power (W)	17	17	17
Voltage - Frequency	120-277V 50-60Hz	120-277V 50-60Hz	120-277V 50-60Hz
Color Temp. (ANSI)	Warm White 3000K	Neutral White 3500K	Cool White 4000K
CRI (Ra)	80	80	80
Typical lumens (lm)	2000	2050	2100
Efficacy (LPW)	118	121	124
Light Emitting Area	280°	280°	280°
Beam Angle	120°	120°	120°
Dimmable	Yes	Yes	Yes
Power Factor	0.9	0.9	0.9
THD	<20%	<20%	<20%
Rated Lifetime - L70 (hrs.)	50,000	50,000	50,000
Dia. x MOL	1.71"x22.48" (44x571mm)	1.71"x22.48" (44x571mm)	1.71"x22.48" (44x571mm)
Weight (lb. / g)	0.31lb. / 140g	0.31lb. / 140g	0.31lb. / 140g

Ref.# DS087-PLL-17W-DIR

### BALLAST PERFORMANCE

Bare Lamp (W)	System (W)	3000K Lumens	3500K Lumens	4000K Lumens
17	21	2000	2050	2100

\* Suitable for use in totally enclosed fixtures

\*\* Specification data is preliminary and may be subject to change

\*\*\* Suitable for damp locations. Not for use where directly exposed to the weather or water