

MR16 Specifier Brass Bullet

Key Features:

- Cast aluminum material
- Tempered, shock and heat resistant lens.
- High temperature socket.
- Angle or Flat Snoot Option

Halogen: FL-501B-MR16

LED: FL-501B-MR16

Halogen

Model#: FL-501B-MR16

Size: 5 1/2" w x 2 1/4" h

Material: Solid Brass

Finish: Bronze

Mounting: 1/2" NPT stake included

Lens: Tempered Flat Clear

Max Lamp: 35W MR16-Not Included

Electrical: 12V AC

Light Spread: Up to 30 ft. x 40 degree

Lumens: 525 avg.

Lamp Life: 4,000 hours avg.

Snoot: Angle or Flat Option

LED

Model#: FL-501B-MR16-LED

Size: 5 1/2" w x 2 1/4" h

Material: Solid Brass

Finish: Bronze

Mounting: 1/2" NPT stake included

Lens: Tempered Flat Clear

Electrical: 9v – 15v AC

Max Lamp: 5.5w MR16-LED

Kelvin: 3000k, Warm White-Standard

Compare to: 42w

Light Spread: Up to 30 ft. x 40 degree

Lumens: 430 avg.

Lamp Life: 30,000 hours avg.

Snoot: Angle or Flat Option

