PLL 14.5W DIR TITANIUM LED SERIES

Preliminary Specifications









- Direct
 Direct
 Direct
- Exceptional efficacy 107 LPW
- Suitable for use in totally enclosed fixtures
- U Wide beam design: 200° beam angle
- **0** 0-10V dimming



PRO

























EFFICIENCY AT WORK



PLL 14.5W DIR TITANIUM LED SERIES

Preliminary Specifications



SPECIFICATIONS**

Product Model	97750 14.5PLL/835/DIR
Туре	PLL
Base	2G11
Power (W)	14.5
Voltage - Frequency	120-277V 50-60Hz
Color Temp. (ANSI)	Neutral White 3500K
CRI (Ra)	80
Typical lumens (lm)	1550
Efficacy (LPW)	107
Light Emitting Area	325°
Beam Angle	200°
Dimmable	Yes
Power Factor	0.9
THD	<20%
Rated Lifetime - L70 (hrs.)	50,000
Dia. x MOL	1.71"x16.54" (44x420mm)
Weight (lb. / g)	0.31lb. / 140g

^{*} Suitable for use in totally enclosed fixtures

^{**} Specification data is preliminary and may be subject to change
*** Suitable for damp locations. Not for use where directly exposed to the weather or water