

2X2' 32W TROFFER TITANIUM LED SERIES



Preliminary Specifications



PRO



- ⌚ Exceptional efficacy meets DLC Premium requirements
- ⌚ High performance lighting distribution and low glare lens
- ⌚ 120-277V circuit and 0-10V dimming control compatible
- ⌚ Modern look and high quality architectural finish
- ⌚ Easy installation for new construction or retrofit



EFFICIENCY AT WORK



2X2' 32W TROFFER TITANIUM LED SERIES

Preliminary Specifications



SPECIFICATIONS*

Product Model	97787 32TROF22DIM/830/277V (MTO)	97788 32TROF22DIM/835/277V	97789 32TROF22DIM/840/277V	97790 32TROF22DIM/850/277V (MTO)
Type	2x2' Troffer	2x2' Troffer	2x2' Troffer	2x2' Troffer
Power (W)	32	32	32	32
Voltage - Frequency	120-277V 50-60Hz	120-277V 50-60Hz	120-277V 50-60Hz	120-277V 50-60Hz
Color Temp. (ANSI)	Warm White 3000K	Neutral White 3500K	Cool White 4000K	Daylight 5000K
CRI (Ra)	80	80	80	80
Typical lumens (lm)	3300	3425	3520	3615
Efficacy (LPW)	103	107	110	113
Beam Angle	120°	120°	120°	120°
Dimmable	Yes	Yes	Yes	Yes
Power Factor	0.9	0.9	0.9	0.9
THD	<20%	<20%	<20%	<20%
Rated Lifetime - L70 (hrs.)	50,000	50,000	50,000	50,000
Dia. x MOL	23.78"x23.78" (604x604mm)	23.78"x23.78" (604x604mm)	23.78"x23.78" (604x604mm)	23.78"x23.78" (604x604mm)
Weight (lb. / g)	8.95lb / 4.06kg	8.95lb / 4.06kg	8.95lb / 4.06kg	8.95lb / 4.06kg

* Specification data is preliminary and subject to change

** Not intended for use in totally enclosed fixtures

*** Suitable for damp locations. Not for use where directly exposed to the weather or water

Ref.:# DS108-TROF-32W-2X2