

PLS 3.5W BYP 2G7 TITANIUM LED SERIES

Preliminary Specifications



3.5W REPLACES



9W
CFL

60% Energy Savings

PRO



- ⌚ Built-in universal voltage driver - Bypass installation
- ⌚ 180° rotatable base
- ⌚ Exceptional efficacy 86 LPW
- ⌚ Last 4 times longer than CFL
- ⌚ Compact form factor fits most fixtures
- ⌚ Suitable for use in totally enclosed fixtures



COMPACT FORM FACTOR AND ROTATABLE BASE SUITABLE FOR ALL APPLICATIONS



PLS 3.5W BYP 2G7 TITANIUM LED SERIES

Preliminary Specifications



APPLICATIONS

Office



Hospitality



General



Ref.#DS106-PLS-3.5W-BYP-2G7

Base: 2G7 (4-pin CFL)
Voltage: 120V - 277V
Dimmable: No
PF: 0.9
Lifetime: 40,000 hrs
Weight: 0.06lb. / 26g



SPECIFICATIONS**

Model	Product	Power (W)	CCT	CRI (typ.)	Lumens	LPW	Beam Angle
3.5PLS/835/BYP/2G7	57818	3.5	Neutral White 3500K	80	300	86	120°

* Suitable for use in totally enclosed fixtures

** Specification data is preliminary and may be subject to change

*** Suitable for damp locations. Not for use where directly exposed to weather or water

**** Full installation guide and more details available on website