

2X4' 40W TROFFER TITANIUM LED SERIES


Preliminary Specifications



PRO



- ⌚ Exceptional efficacy meets DLC Premium requirements
- ⌚ High performance lighting distribution and low glare lens
- ⌚ 120-277V circuit and 0-10V dimming control compatible
- ⌚ Modern look and high quality architectural finish
- ⌚ Easy installation for new construction or retrofit



EFFICIENCY AT WORK



2X4' 40W TROFFER TITANIUM LED SERIES

Preliminary Specifications



SPECIFICATIONS*

Product Model	97791 40TROF24DIM/830/277V (MTO)	97792 40TROF24DIM/835/277V	97793 40TROF24DIM/840/277V	97794 40TROF24DIM/850/277V (MTO)
Type	2x4' Troffer	2x4' Troffer	2x4' Troffer	2x4' Troffer
Power (W)	40	40	40	40
Voltage - Frequency	120-277V 50-60Hz	120-277V 50-60Hz	120-277V 50-60Hz	120-277V 50-60Hz
Color Temp. (ANSI)	Warm White 3000K	Neutral White 3500K	Cool White 4000K	Daylight 5000K
CRI (Ra)	80	80	80	80
Typical lumens (lm)	4120	4280	4400	4520
Efficacy (LPW)	103	107	110	113
Beam Angle	120°	120°	120°	120°
Dimmable	Yes	Yes	Yes	Yes
Power Factor	0.9	0.9	0.9	0.9
THD	<20%	<20%	<20%	<20%
Rated Lifetime - L70 (hrs.)	50,000	50,000	50,000	50,000
Dia. x MOL	23.94"x47.72" (608x1212mm)	23.94"x47.72" (608x1212mm)	23.94"x47.72" (608x1212mm)	23.94"x47.72" (608x1212mm)
Weight (lb. / g)	15.34lb / 6.96kg	15.34lb / 6.96kg	15.34lb / 6.96kg	15.34lb / 6.96kg

* Specification data is preliminary and subject to change

** Not intended for use in totally enclosed fixtures

*** Suitable for damp locations. Not for use where directly exposed to the weather or water

Ref.:# DS109-TROF-40W-2X4