

2X2' 30W RETROFIT KIT TITANIUM LED SERIES





Preliminary Specifications

PRO



- ⌚ Easy 3-5 minutes tool-less installation
- ⌚ Universally compatible to upgrade 2x2' troffer and louver
- ⌚ Exceptional efficacy meets DLC Premium requirements
- ⌚ 120-277V circuit and 0-10V dimming control compatible
- ⌚ High performance lighting distribution and low glare lens
- ⌚ Modern look and high quality architectural finish



EFFICIENCY AT WORK



2X2' 30W RETROFIT KIT TITANIUM LED SERIES



Preliminary Specifications

SPECIFICATIONS*

Product Model	97795 30TROFKIT22DIM/830/277V	97796 30TROFKIT22DIM/835/277V	97797 30TROFKIT22DIM/840/277V	97798 30TROFKIT22DIM/850/277V (MTO)
Type	2x2' Troffer Retrofit Kit	2x2' Troffer Retrofit Kit	2x2' Troffer Retrofit Kit	2x2' Troffer Retrofit Kit
Power (W)	30	30	30	30
Voltage - Frequency	120-277V 50-60Hz	120-277V 50-60Hz	120-277V 50-60Hz	120-277V 50-60Hz
Color Temp. (ANSI)	Warm White 3000K	Neutral White 3500K	Cool White 4000K	Daylight 5000K
CRI (Ra)	80	80	80	80
Typical lumens (lm)	3090	3210	3300	3390
Efficacy (LPW)	103	107	110	113
Beam Angle	120°	120°	120°	120°
Dimmable	Yes	Yes	Yes	Yes
Power Factor	0.9	0.9	0.9	0.9
THD	<20%	<20%	<20%	<20%
Rated Lifetime - L70 (hrs.)	50,000	50,000	50,000	50,000
Dia. x MOL	23.94"x23.90" (608x607mm)	23.94"x23.90" (608x607mm)	23.94"x23.90" (608x607mm)	23.94"x23.90" (608x607mm)
Weight (lb. / g)	6.92lb / 3.14kg	6.92lb / 3.14kg	6.92lb / 3.14kg	6.92lb / 3.14kg

* Specification data is preliminary and subject to change

** Not intended for use in totally enclosed fixtures

*** Suitable for damp locations. Not for use where directly exposed to the weather or water

Ref.:# DS110-TROFKIT-30W-2X2