

Contractor Select™ LED Wraparounds

LBL LED

SBL LED

Familiar Design. New Technology.

Update to LED without breaking the bank!

The Contractor Select SBL LED and LBL LED wraparounds from Lithonia Lighting® present two affordable LED solutions for general-purpose ambient lighting. These two products provide a similar look to that of a traditional fluorescent wrap with all the great benefits of LED and are priced for the budget-conscious.

SBL & LBL Contractor Select Options

| Catalog Number | Size | CCT | Wattage | Lumens* | Pallet Qty | Savings w/LED** |
|--------------------------|------|---------------|---------|---------|------------|-----------------|
| SBL2 LP835 or SBL2 LP840 | 2' | 3500 or 4000K | 23 | 2400 | 140 | 47% |
| SBL4 LP835 or SBL4 LP840 | 4' | 3500 or 4000K | 39 | 4500 | 70 | 45% |
| LBL2 LP835 or LBL2 LP840 | 2' | 3500 or 4000K | 23 | 2250 | 112 | 47% |
| LBL4 LP835 or LBL4 LP840 | 4' | 3500 or 4000K | 41 | 4600 | 56 | 45% |

* Nominal Lumen Output
** Energy Savings over T12 Fluorescent.

LED Technology

- Designed to replace existing 2-lamp T8 and T12 fluorescent
- Standard MVOLT (120-277) dimming driver
- Available in two CCTs: 3500K and 4000K
- Long-life LEDs
- Ideal for: closets, storage rooms, hallways and office spaces



CONTRACTOR SELECT


SBL LED & LBL LED Configurable Wraparounds

Configurable. Specifiable. Affordable.

The SBL LED and LBL LED wraparounds from Lithonia Lighting® provide multiple LED options for general-purpose ambient lighting. With a wide range of lumen packages, configurations and control options, these luminaires allow for a one-for-one replacement of an existing wrap without disrupting the look of your overall space.

Dimming & Control Options

Standard eldoLED® 1% dimming (EZ1) provides smooth, seamless and flicker-free 0-10V dimming. These advanced dimming capabilities save energy and prolong the life of the LEDs while taking advantage of the LED's dimming capabilities.



Pair the SBL LED or LBL LED with the LSXR fixture-mount occupancy sensor for additional energy savings. The LSXR can dim the luminaire down to a low-level setting or turn the luminaire completely off when there is no occupancy.

On-board nLight® digital technology allows the luminaire to communicate with control devices such as occupancy sensors, photocells and wall stations. With unmatched flexibility, nLight easily scales from one room to an entire campus.



Lumen Packages

- SBL2 & LBL2 - 2000 lumens
- SBL4 & LBL4 - 3000, 4000, 4800, 6000, 7200 lumens
- LBL4W - 6500, 8000 lumens
- Designed to replace 2-lamp to 4-lamp fluorescent

Color Temperatures (CCTs)

For design flexibility, the LED wraparounds are offered in four color temperatures: 3000K, 3500K, 4000K and 5000K (CRI 82)

Performance

- Delivers over 100 LPW consistently
- 90% LED lumen maintenance at 60,000 hours (L90/60,000)

Options

- Integrated emergency battery pack



DesignLights Consortium® (DLC) qualified product. Not all versions of this product may be DLC qualified. Please check the DLC Qualified Products List at www.designlights.org/QPL to confirm which versions are qualified.

eldoLED

Configurable Options

SBL 2' & 4'



LBL 2' & 4'



LBLW wide housing 4'

