83718 30W BULLET FLOOD LIGHT

TECHNICAL DATA SHEET

FEATURES




- \bullet Energy efficient; consumes at least 50% less than traditional lighting.
- Low working temperature.
- Lifespan of 50,000 hours
- IP rating: IP54, wet locations

APPLICATION:

Landscaping lighting







SPECIFICATIONS								
Power Consumption	30W							
Input Voltage	100-277VAC							
Input Currant	0.5A @100V / 0.2A @277V							
Power Factor	≥ 0.95							
Lumens	2300							
Luminous Efficiency	75Lm/W							
Color Temperature	3000K							
CRI	70							
Beam Angle	140°							
Construction	Aluminium Tempered Glass							
Dimension (Inches)	8"(H) x 7.76"(D) x 5.18"(DIA)							
LED DRIVER								
Output Voltage	24-45VDC							
Output Current	0.7A							
Driver Efficiency	88%							
LED								
LED Type	CXA1512							
LED Quantity	1 pcs							
LED Chip Manufacturer	Cree							
LED Efficiency	120Lm/W							
LIFESPAN & ENVIRONMENT								
Lifespan (Hours)	50,000							
Operating Temperature	-20°C - +40°C							
SAFETY & EMC								
Withstand Voltage	I/P-FG: 2121VDC							
Grounding Resistance	25A 100mΩ							
Electromagnetic Compatibility	EN55015, EN61000-2-3, EN61000-3-3, EN61547							



ORDERING

ITEM#	DESCRIPTION	WATTS	COLOR	LUMENS	CRI	VOLTS	HOUSING	HOURS	CASE
83718	LED 30W BULLET FLOOD/30K/100-277V - SUPERIOR LIFE®	30	3000K	2300	70	100-277	BRONZE	50,000	6