


LED T8 LINEAR TUBES — Plug-n-Play



- Direct replacement (Plug-n-Play)
- Full Glass Housing:
No Aging/Yellowing, Bending
- Compatible with instant start, rapid start, programmed start and dimmable electronic ballasts
- Shatterproof is available with NSF Certificate (special order except for 96")
- Warranty: 5 years/50,000 hours



Ordering Code	Description	Watts (W)	Nom. Length (in)	Approx Lumens (lm)	Color Temp (K)	Beam Angle	CRI	Base	Avg Life (hrs)
64540-GEN	LED 9T8/24/830 DR	9	24	1150	3000	230°	83	G13	50,000
64541-GEN	LED 9T8/24/835 DR	9	24	1150	3500	230°	83	G13	50,000
64542-GEN	LED 9T8/24/840 DR	9	24	1150	4000	230°	83	G13	50,000
64543-GEN	LED 9T8/24/850 DR	9	24	1150	5000	230°	83	G13	50,000
64545-GEN	LED 11T8/36/830 DR	11	36	1450	3000	230°	83	G13	50,000
64546-GEN	LED 11T8/36/835 DR	11	36	1450	3500	230°	83	G13	50,000
64547-GEN	LED 11T8/36/840 DR	11	36	1450	4000	230°	83	G13	50,000
64548-GEN	LED 11T8/36/850 DR	11	36	1450	5000	230°	83	G13	50,000
64549-GEN	LED 12T8/48/830 DR	12	48	1800	3000	230°	83	G13	50,000
64550-GEN	LED 12T8/48/835 DR	12	48	1800	3500	230°	83	G13	50,000
64551-GEN	LED 12T8/48/840 DR	12	48	1800	4000	230°	83	G13	50,000
64536-GEN	LED 12T8/48/850 DR	12	48	1800	5000	230°	83	G13	50,000
64553-GEN	LED 14T8/48/830 DR	14	48	1800	3000	230°	83	G13	50,000
64552-GEN	LED 14T8/48/835 DR	14	48	1800	3500	230°	83	G13	50,000
64539-GEN	LED 14T8/48/840 DR	14	48	1800	4000	230°	83	G13	50,000
64538-GEN	LED 14T8/48/850 DR	14	48	1800	5000	230°	83	G13	50,000
64537-GEN	LED 17T8/48/830 DR	17	48	2200	3000	230°	83	G13	50,000
64532-GEN	LED 17T8/48/835 DR	17	48	2200	3500	230°	83	G13	50,000
64533-GEN	LED 17T8/48/840 DR	17	48	2200	4000	230°	83	G13	50,000
64534-GEN	LED 17T8/48/850 DR	17	48	2200	5000	230°	83	G13	50,000
64555-GEN	LED 24T8/96/830 DR*	24	96	3500	3000	230°	83	FA8	50,000
64556-GEN	LED 24T8/96/835 DR*	24	96	3500	3500	230°	83	FA8	50,000
64557-GEN	LED 24T8/96/840 DR*	24	96	3500	4000	230°	83	FA8	50,000
64558-GEN	LED 24T8/96/850 DR*	24	96	3500	5000	230°	83	FA8	50,000
64554-GEN	LED 35T8/96/830 DR*	33	96	4400	3000	230°	83	FA8	50,000
64528-GEN	LED 35T8/96/835 DR*	33	96	4400	3500	230°	83	FA8	50,000
64527-GEN	LED 35T8/96/840 DR*	33	96	4400	4000	230°	83	FA8	50,000
64526-GEN	LED 35T8/96/850 DR*	33	96	4400	5000	230°	83	FA8	50,000

*Shatterproof

Green Energy Lighting Corp

11266 Monarch Street Garden Grove, CA 92841

P 714.889.4101 F 714.889.4128 www.greenenergylight.com

Specifications may be subject to change without prior notice.