



POWER YOU CAN DEPEND ON

Milbank PowerGen™'s level II electric vehicle car charger delivers a full charge to your electric vehicle (EV) or plug-in electric vehicle (PHEV) in just a few hours. With AC power, electricity is transferred from the charging station to your car's on-board charger.

This space-saving, wall-mounted design is ideal for your home garage - conveniently charge your vehicle while sleeping, enjoying a meal or spending time with friends and family.







WALL-MOUNTED CHARGING DOCKS



FEATURES

SPECIFICATIONS	
Model Number	MEVSE-RS
Connector	SAE J1772
Voltage	208VAC to 240VAC
Frequency	50Hz / 60Hz
Current	30A max
Operating Temper-	-30°C to 50°C
ature	-22°F to 122°F
Storage/Transit	-40°C to 60°C
Temperature	-40°F to 160°F
Humidity	Up to 95% non-con-
	densing
Dimensions	12" x 12" x 8"
(L x W x H)	(approximate)
Weight	10 lbs. (excluding
	cable)
Cord Length	Up to 25' available
Enclosure	NEMA 4

Note: Milbank reserves the right to make changes in specifications and features shown without notice or discontinue the product described at any time without notice or obligation.

- Industry standard SAE J1772 connector
- Auto restart in event of power outage or ground fault
- Americans with Disabilities Act (ADA) compliant installation
- Integrated cable stowage
- Underwriters Laboratory (UL) listed
- Breakaway safety cable
- Optional pedestal mount
- Weather-resistant NEMA 4 enclosure
- 3-year warranty (parts)





