

LED-8084M Post Top / Site / Wall Pack

SKU (USA)

LED-8084M30
LED-8084M42
LED-8084M57


Description

45W 3000K with External Driver
45W 4200K with External Driver
45W 5700K with External Driver

Technical Specifications

Models US/CAN	LED-8084M30	LED-8084M42	LED-8084M57
CCT	3000K	4200K	5700K
Power Consumption	45 watts		
Replaces	175w MH/HPS		
Mounting	E39		
Voltage	120-277VAC (USA)		
LED Type	Samsung #5630 SMD		
Beam Angle	360		
Dimmable	Yes		
Operating Temp	-40°F - +122°F		
Rated R70 Life	Up to 50,000 Hrs.		
Warranty	5 Year Limited*		
LM79 Specifications	Yes	Yes	Yes
Power (W)	43.5	44.1	43.8
CCT	3136	4085	5782
Light Output	4062	4273	4509
Efficacy	93.4	96.9	102.7
THD @ 120V	n/a	n/a	n/a
THD @ 277V	12.70%	12.70%	12.60%
PF @ 120V	n/a	n/a	n/a
PF @ 277V	0.918	0.921	0.919
CRI:	84.4	84.4	85.8
R9	18	27	11
Duv	-0.0005	-0.0005	0.0024
Packaging	4 / Master Carton		
Unit	7.5" x 5.44" x 12" 3.99 lbs.		
Master	15.8" x 11.6" x 12.6" 25.5 lbs.		

Note: All specification information falls within a $\pm 2\%$ range and is subject to change without notice.
NOTE: Light Efficient Design is providing this information to the general public. Please note that all products contained herein are trademarked, copyrighted, and/or have patents pending. Any use of these designs is strictly prohibited without prior written consent. Light Efficient Design protects its proprietary information vigorously in the courts of the United States of America.



HID-X
• EXTERNAL DRIVER LED
• IP65 RATING
• 0-10V / PWM DIMMING

45W
LED for HID

Replaces
175W
MH / HPS



Description:

45W LED retrofit lamp to replace MH and HPS lamps up to 175w, E39 Mogul base. UL wet rated and approved for open or fully enclosed fixtures.

Features:

- Replaces up to 175w HID Lamps
- 120-277V
- Meanwell PWM & 0-10V Dimmable driver
- Driver can be mounted up to 20 meters from lamps with negligible reduction in light output.
- UL approved for both open and fully enclosed fixtures within wet locations (USA & Canada)
- 50,000 HR rated LED life
- 5 year limited warranty (*see website for details)

Applications:



Wall Pack



Shoe Box



Post Top

Installation Notes:

- When installing LED-8000 series retrofit lamps within HID fixtures, **ballast must be bypassed** when present.
- 8000 series retrofits are UL damp rated, sealing the fixtures after installation will deliver best results.
- **Installing surge/lightning protectors is highly recommended** and helps to eliminate premature driver failure caused by surges and other power fluctuations.