


# LEDme® PRO AC-LED LIGHT BARS

## BA-ACLED

# WAC LIGHTING

Responsible Lighting®



### PRODUCT DESCRIPTION

Bringing out the best in bold, eye-catching residential, retail and commercial displays, LEDme® PRO AC-LED Light Bars are ideal for counters and cabinets. Thermally efficient, these fixtures are crafted for illuminating heat sensitive perishables and color sensitive apparel, artwork and collectibles.

### FEATURES

- High CRI 90+
- Does not require any driver or transformer
- True 1" profile
- Backlighting with parabolic reflector allows a high uniformity of light
- Each light bar includes one "I" connector
- Minimal space between diffusers for a visually seamless line of illumination
- Free of projected heat, UV and IR radiation
- 90,000 hour rated life
- 5 year WAC Lighting product warranty

### SPECIFICATIONS




- Construction:** Extruded aluminum body with polycarbonate lens.
- Power:** Direct 120VAC 60Hz input.
- Light Source:** 2700K or 3000K AC LEDs. CRI: 90.
- Dimming:** May be dimmed down to 10% with electronic low voltage (ELV) dimmer. Compatible with *LUTRON DVELV-300, SELV-300* Electronic Low Voltage dimmer
- Finish:** Abrasion resistant Bronze (BZ), Brushed Aluminum (AL) and White (WT) powder coat.
- Standards:** Title 24 CEC Compliant. Energy Star Rated. ETL & cETL Listed.

### FIXTURE PERFORMANCE

Model #	Color Temp	Power	Lumens	Efficacy
<b>BA-ACLED8-927</b>	2700K	5.5W	250	45 Lm/W
<b>BA-ACLED8-930</b>	3000K	5.5W	255	46 Lm/W
<b>BA-ACLED12-927</b>	2700K	8W	360	45 Lm/W
<b>BA-ACLED12-930</b>	3000K	8W	365	46 Lm/W
<b>BA-ACLED18-927</b>	2700K	10W	445	45 Lm/W
<b>BA-ACLED18-930</b>	3000K	10W	450	45 Lm/W
<b>BA-ACLED24-927</b>	2700K	15W	700	47 Lm/W
<b>BA-ACLED24-930</b>	3000K	15W	705	47 Lm/W
<b>BA-ACLED30-927*</b>	2700K	17W	765	45 Lm/W
<b>BA-ACLED30-930*</b>	3000K	17W	785	46 Lm/W

\* Not Title 24 compliant

### ACCESSORIES

6' power cord		<b>BA-PC6-WT</b>	Supplies power in any application.
"I" connector		<b>BA-I-WT</b>	Interconnection for seamless end to end transitions. One included with each light bar.
Interconnect cable		<b>BA-IC12-WT</b> <b>BA-IC24-WT</b> <b>BA-IC36-WT</b>	12" 24" 36" Links two light bars using a single power connection.

### ORDER NUMBER

Model#	Length	Color Temp	Finish
<b>BA-ACLED</b>	<b>8</b> 8"	<b>927</b> 2700K <b>930</b> 3000K	<b>BZ</b> Bronze <b>AL</b> Brushed Aluminum <b>WT</b> White
	<b>12</b> 12"		
	<b>18</b> 18"		
	<b>24</b> 24"		
	<b>30</b> 30"		

### FINISHES



**BA-ACLED** [ ] - [ ] - [ ]

Example: **BA-ACLED12-927-AL**