


LEDme® PRO AC-LED LIGHT BARS

BA-ACLED

WAC LIGHTING

Responsible Lighting®



PRODUCT DESCRIPTION

Bringing out the best in bold, eye-catching residential, retail and commercial displays, LEDme® PRO AC-LED Light Bars are ideal for counters and cabinets. Thermally efficient, these fixtures are crafted for illuminating heat sensitive perishables and color sensitive apparel, artwork and collectibles.

FEATURES

- High CRI 90+
- Does not require any driver or transformer
- True 1" profile
- Backlighting with parabolic reflector allows a high uniformity of light
- Each light bar includes one "I" connector
- Minimal space between diffusers for a visually seamless line of illumination
- Free of projected heat, UV and IR radiation
- 90,000 hour rated life
- 5 year WAC Lighting product warranty

SPECIFICATIONS




- Construction:** Extruded aluminum body with polycarbonate lens.
- Power:** Direct 120VAC 60Hz input.
- Light Source:** 2700K or 3000K AC LEDs. CRI: 90.
- Dimming:** May be dimmed down to 10% with electronic low voltage (ELV) dimmer. Compatible with *LUTRON DVELV-300, SELV-300* Electronic Low Voltage dimmer
- Finish:** Abrasion resistant Bronze (BZ), Brushed Aluminum (AL) and White (WT) powder coat.
- Standards:** Title 24 CEC Compliant. Energy Star Rated. ETL & cETL Listed.

FIXTURE PERFORMANCE

| Model # | Color Temp | Power | Lumens | Efficacy |
|------------------------|------------|-------|--------|----------|
| BA-ACLED8-927 | 2700K | 5.5W | 250 | 45 Lm/W |
| BA-ACLED8-930 | 3000K | 5.5W | 255 | 46 Lm/W |
| BA-ACLED12-927 | 2700K | 8W | 360 | 45 Lm/W |
| BA-ACLED12-930 | 3000K | 8W | 365 | 46 Lm/W |
| BA-ACLED18-927 | 2700K | 10W | 445 | 45 Lm/W |
| BA-ACLED18-930 | 3000K | 10W | 450 | 45 Lm/W |
| BA-ACLED24-927 | 2700K | 15W | 700 | 47 Lm/W |
| BA-ACLED24-930 | 3000K | 15W | 705 | 47 Lm/W |
| BA-ACLED30-927* | 2700K | 17W | 765 | 45 Lm/W |
| BA-ACLED30-930* | 3000K | 17W | 785 | 46 Lm/W |

* Not Title 24 compliant

ACCESSORIES

| | | | |
|--------------------|--|---|--|
| 6' power cord |  | BA-PC6-WT | Supplies power in any application. |
| "I" connector |  | BA-I-WT | Interconnection for seamless end to end transitions. One included with each light bar. |
| Interconnect cable |  | BA-IC12-WT BA-IC24-WT BA-IC36-WT | 12" 24" 36" Links two light bars using a single power connection. |

ORDER NUMBER

| Model# | Length | Color Temp | Finish |
|-----------------|---------------|--------------------------------------|---|
| BA-ACLED | 8 8" | 927 2700K 930 3000K | BZ Bronze AL Brushed Aluminum WT White |
| | 12 12" | | |
| | 18 18" | | |
| | 24 24" | | |
| | 30 30" | | |

FINISHES



BA-ACLED [] - [] - []

Example: **BA-ACLED12-927-AL**