



GE132MAXP-N/ULTRA (replaces GE132MAX-N/ULTRA)

72259

GE LFL UltraMax™ Professional Series Electronic High Efficiency Multivolt Instant Start Ballast

Features & Benefits

- Energy saving high efficiency instant start electronic ballast (> 90%)
- Multi-Voltage Technology handles voltage from 120 to 277V
- UL Type CC Rating provides protection against arcing in electrical devices.
- Anti-Striation Control for better light quality, with no striations.
- Cold temperature -20F Minimum Starting Temperature

Specifications

GENERAL CHARACTERISTICS

Ambient Temp [Max]	131 °F
Ambient Temp [Min]	-22 °F
Ballast Factor	Normal
Ballast Type	High Efficiency Multivolt Instant Start
Case Temperature (Max)	70 °C
Classification (Regulations)	cUL Listed FCC - CLASS A Non-Consumer UL Class P UL Listed UL Type 1 Outdoor UL Type CC UL Type HL NEMA Premium® Product is compliant with material restriction requirements of RoHS
Sound Rating	A (20-24 decibels)
Starting Method	Instant start
Product Technology	Linear Fluorescent
Lamp Wiring	Parallel
Power Factor Correction	Active

ELECTRICAL CHARACTERISTICS

Supply Current Frequency	50
--------------------------	----

DIMENSIONS

Weight	0.6 lb
Exit Type	
Remote Mount Distance	18.0 ft

PACKAGING INFORMATION

Alternative Unit Of Measure	CASE
Standard Package Quantity	10
Ean UPC	043168722599
Standard Package GTIN	10043168722596
Length	9.93 in
Width	10.12 in
Height	3.51 in
Volume	0.20412 cuft
Gross Weight	11.67 lb
Pack Level Description	Case
Sales Unit	Case
UCC	043168722599

BALLAST DIMENSION

Case dimensions	
Length	9.5 in
Width	1.3 in
Height	1.0 in
Mounting dimensions	
Mount Length	8.89 in
Mount Width	0.88 in
Mount Slots	0.312 in

LEAD LENGTH

Lead Color	Quality of Leads Per Color	Lead Exit Type	Lead Size	Lead Length
Black	1	Left	25	25 in
Red	1	Right	45	45 in
Blue	1	Right	31	31 in
White	1	Left	25	25 in