## **TRACK CONNECTORS**

## WAC LIGHTING

Responsible Lighting®

## 120V Track System



Track Connectors		Model			Finish		Description
Live End Connector		HLE LLE JLE J2-LE	H Track L Track J Track J2 Track	4¼" × 1¾" × ¾" 4¼" × 1¾" × ¾" 4¾" × 1¼" × ¾" 4¾" × 1¼" × ¾"			Use for direct wiring through ceiling. A canopy plate is required when using with a standard junction box.
Live End BX Connector		HBXLE LBXLE JBXLE J2-BXLE	H Track L Track J Track J2 Track	6"×1%"×1¼" 5¾"×1¾"×1¼" 6¼"×1¾"×1¼" 5%"×1¾"×1¼"			Use with surface mounted BX or non-metallic sheathed cable. Also provides through the ceiling connection.
"I" Power Connector		HI-PWR LI-PWR JI-PWR J2-IPWR	H Track L Track J Track J2 Track	6¾"×1¾"×¾" 7"×1¾"×¾" 7½"×1¾"×¾" 7"×1¾"×¾"			Power entry point at the connection of 2 tracks.
"L" Connector Left		HL-LEFT LL-LEFT JL-LEFT J2-LLEFT	H Track L Track J Track J2 Track	2¾" × 2¾" × ¾" 4½" × 4½" × ¾" 4½" × 4½" × ¾" 4½" × 4½" × ¾"	BN* WT	Black Brushed Nickel White Dark Bronze	Use to join 2 track sections to make power feedable 90° left polarity turns.
"L" Connector Right		HL-RIGHT LL-RIGHT JL-RIGHT J2-LRIGHT	H Track L Track J Track J2 Track	2¾" × 2¾" × ¾" 4¼" × 4¼" × ¾" 4¼" × 4¼" × ¾" 4¼" × 4¼" × ¾"			Use to join 2 track sections to make power feedable 90° right polarity turns.
"T" Connector		HT LT JT J2-T	H Track L Track J Track J2 Track	4" × 2¾" × ¾" 7¼" × 4¼" × ¾" 7½" × 4¼" × ¾" 7"× 4¼" × ¾"			Use to join 3 track sections. Power feedable on H and J only. "T" Connector with opposite polarity can be custom ordered.
"X" Connector		HX LX JX J2-X	H Track L Track J Track J2 Track	4½" × 4½" × ¾" 7½" × 7½" × ¾" 7½" × 7½" × ¾" 7½" × 7½" × ¾" 7" × 7" × ¾"			Use to join 4 track sections. Power feedable on H and J only.
"I" Connector		HI LI JI J2-I	H Track L Track J Track J2 Track	3"×1%"×¾" 3½"×1½"×¾" 3"×1½"×¾" 4½"×1½"×¾"			Use to join two sections of track with electrical continuity.
"I" Dead End Connector	S.	HI-DEC LI-DEC JI-DEC J2-IDEC	H Track L Track J Track J2 Track	3"×1%"×¾" 3½"×1¾"×¾" 3"×1¾"×¾" 3½"×1¾"×¾"			Joins two sections of track without electrical continuity.
Flexible Track Connector		HFLX LFLX JFLX J2-FLX	H Track L Track J Track J2 Track	11"×1%"×¾" 9¾"×1%"×¾" 8½"×1%"×¾" 11½"×1%"×¾"			Connects two track sections at variable angles. Use as a transition from wall-to-wall, wall-to-ceiling, or ceiling-to-ceiling. Power feedable.
Floating Canopy Connector	Can.	HFC LFC JFC	H Track L Track J Track	4½" × 4½" × 1½" 4¼" × 4¼" × 1¾" 4½"× 45%" × 13%"			Connects to octagon box. Allows track to be powered anywhere along the length of the track.

**<sup>\*</sup>BN** finish only available for H, L, J Track **\*\*DB** finish only available for H Track