

SPECIFICATIONS

Item #902682



Galaxy® DE Select-A-Watt® 600/750/875/1000/Turbo Charge® Electronic Ballast



GALAXY® DE

This document is not intended to be used for installation purposes. We cannot cover all specific applications or anticipate all requirements. All specifications are subject to change without notice.

• = yes

•	ETL LISTED
	Tested to UL Standard #1029 Tested to CSA Standard C22.2 No. 74
LAMP COMPATIBILITY	
•	Double Ended HPS - Max. Wattage: 1000
TRANSFORMER VOLTAGE	
•	120 / 240
	240 ONLY
	277 ONLY
	480 ONLY
	AMPS AT 120V POWER: 9.10
	AMPS AT 240V POWER: 4.55
	AMPS AT 277V POWER: N/A
	AMPS AT 480V POWER: N/A
	POWER SOURCE khz: 105
	POWER FACTOR (cos ϕ): > 0.99
	AMBIENT TEMPERATURE: 40°C
	TOTAL HARMONIC DISTORTION: < 10%
POWER CORD	
•	DETACHABLE 120 VOLT SMART VOLT*
	HARD WIRED 277 VOLT w/ L7-15p TWIST LOCK PLUG
	HARD WIRED 480 VOLT - WIRE ONLY (NO PLUG)
LAMP CORD RECEPTACLE COMPATIBILITY	
•	DUAL UNIVERSAL
	SUN SYSTEM ONLY
WARRANTY	
	2 YEAR
•	3 YEAR
	5 YEAR

* 240 volt cord sold separately