

LED A19

40W/60W Incandescent equivalent



Product Features

- Available in 2700K/5000K Color Temperature options
- 5.5W A19 delivers 450lm in soft-white
- 9W A19 delivers 900lm.
- Color Rendering index > 82
- Beam angle: 205°
- 10,000 hours rated life, it will last 9.1 years based on 3 hours per day usage
- Limited 5-year replacement warranty
- Instant on - No warm-up period
- Suitable for damp locations
- Contain no harmful lead or mercury
- Non-dimmable

Energy Saving

Bulb Technologies	Annual Electricity Cost	Over 10,000 hours
40W Incandescent	\$4.80	\$44
5.5W LED bulb	\$0.66	\$6.05
<i>Saving per bulb</i>	\$4.14	\$37.95
60W Incandescent	\$7.22	\$66
9W LED bulb	\$1.08	\$9.9
<i>Saving per bulb</i>	\$6.14	\$56.1

Based on 3 hours per day usage and \$0.11 per Kwh.

Caution

1. Suitable for use in operating environments between -20°C and +45°C (-4°F and + 113°F)
2. Not for use with emergency light fixtures or exit lights
3. Use in open fixture or
4. Does not support dimmers.
5. Not suitable for totally enclosed fixtures

Key Technical Data

Curtis Mathes. Life | Always On.™

Models	CMA19-1109-8XX	CMA19-1312-8XX
Rated Wattage	5.5W	9W
Initial Luminous Flux	450lm	800lm
CRI	>82	>82
Beam angle	205°	205°
CCT	2700K/3000K/5000K options	
Efficacy (lm/Watt)	81.8	100
Input Voltage	115V-128V @60Hz	
Dimming	No	No
Incandescent replacement	40W	60W
Bulb shape	A19	A19
MOL	(MOL) 4.2", (bulb diameter) 2.37"	
Rated Life	10,000 hrs	

Packaging Information

Single box dimension	6.2x6.2x10.7cm	6-Pack Case dimension	17.5x11.5x11.5 cm
Master Carton Q'ty	60 pcs	6-Pack Case Gross weight	1.05 lbs (0.48 kg)
Master carton Dimension	33x39.5x23.5cm	Case Q'ty/Master Carton	12 cases
Master carton gross weight	9.9 lbs (4.5kg)	Bulb Q'ty/Master carton	72 units
Bulb Q'ty per GMA Pallet	4860 pcs	Master carton Dimension	54.5x25x25 cm
		Master carton gross weight	52.4 lbs (23.8kg)

Ordering Information

Models	Wattages	Case Q'ty	Color Temperature
CMA19-1109-8XX	5.5W	1	XX = 27 for 2700K
CMA19-1312-8XX	9W	1	XX = 30 for 3000K
CMA19-1312-8XX-6PK	9W	6	XX = 50 for 5000K

UPC Information

CMA19-1312-827	CMA19-1312-850	CMA19-1312-830	CMA19-1312-827-6PK	CMA19-1109-827
				
8 11019 02062 6 8	8 11019 02063 3 8	8 11019 02095 4 8	8 11019 02096 1 8	8 11019 02061 9

Information provided is subject to change without notice. Please verify all details with Curtis Mathes. All values are design or typical values when measured under laboratory conditions, and Curtis Mathes makes no warranty or guarantee, expressed or implied, that such performance will be obtained under end-use conditions