

55209

LED FLAT 2' HIGH BAY/160W

TECHNICAL DATA SHEET

FEATURES



HIGH-BAY LUMINAIRES FOR COMMERCIAL AND INDUSTRIAL BUILDINGS

- Provides smooth uniform light.
- Low-profile which meets limitless range of applications.
- Use 30% less energy than a linear fluorescent fixtures

HOUSING

- Die formed 24 gauge cold rolled steel.
- All steel surfaces are painted after fabrication with high gloss baked white matte powder paint.

MOUNTING

Designed for pendant, chain mounting or adjustable cable.

DIMMING

- 0-10V dimming function, dimming range is 10% - 100%

APPLICATION

Larger warehouses, retail applications, commercial buildings and work areas.




SPECIFICATIONS

Power Consumption	160W
Input Voltage	120-277V
Power Factor	0.9
THD	8.8%
Lumens	19280
Luminous Efficiency	121 Lm/W
Color Temperature	5000K
CRI	80
Beam Angle	120°
Housing	24 Gauge Steel
Finish	White
Dimensions (Inches)	23.8"(L) x 17.3"(W) x 3.6"(D)

LIFESPAN & ENVIRONMENT

Average Life	50,000
Operating Temperature	-20°C ~ 50°C

DIMENSIONS



ORDERING

ITEM#	DESCRIPTION	WATTS	COLOR	LUMENS	CRI	VOLTS	HOURS	CASE
55209	LED FLAT 2' HIGH BAY 160W/5000K/FROSTED LENS/DIMMABLE - SUPERIOR LIFE® DLC	160	5000K	19280	80	120-277	50,000	1
WIRE GUARD ACCESSORY (as shown in image above)								
55211	WIRE GUARD FOR LED FLAT 2' HIGH BAY 160W							1