

# PRIORI T2

High light output and energy savings in a low profile fixture with a modular design.

## Performance

- Warm White light with 90 CRI mimics the look of incandescent but without the heat
- Modular design allows flexibility and easy installation
- Low profile housing hides easily – less than 1" high
- Long life fluorescent T2 lamps are rated for 10,000 hours

## Construction

- Steel housing with powder coat finish
- Prismatic tempered glass lens diffuses light
- Magnetic closure secures cover without clips or tabs that can bend or break

## Installation

- Mount to underside of shelf or cabinet, at the leading edge, for best performance
- Modular design with hardwire junction boxes, power cords and linking cables sold separately offers maximum flexibility and optimal fixture placement
- Quick release clip provides tool-free access to wiring compartment saving time for hardwire installations
- Captive screw design speeds installation



## Specifications

Series	043T
Input voltage	120V AC, 60Hz
Color temperature	3000K
CRI	90+
Wattage	6W / 8W / 13W / 18W / 24W
Lumens	See individual product
Maximum run	600 watts
Beam angle	120°
Dimming	Non-dimming
Housing	Cold rolled steel
Lens	Prismatic tempered glass
Rating	c/UL/us Listed, dry locations
Dimensions	3-3/4"W x 15/16"H x Length
Power input	Hardwire, modular or plug-in
Mounting	Captive screws
Linking	Via 043A linking cables
Lamp type	T2 with axial base, 3000K
Rated life	10,000 hrs

## Building a System

### Determine Layout:

- Determine the quantities and lengths of fixtures needed.
- Determine power input:
  1. Hardwire via knockouts
  2. Modular with junction box
  3. Plug-in

### Select Power Input Accessories:

1. Hardwire via knockouts: no additional accessories needed
2. Modular with junction box: use ALC-BOX with 12" jumper
3. Plug-in: use ALC-PC6, one per fixture or one for first fixture and link subsequent

### Select Linking Accessories:

1. Direct end-to-end: no additional accessories needed
2. Linking cables: Choose 6", 12", 24" or 36" jumpers (043A linking cables)



Priori T2 - Dark Bronze

**043T-10-DB**

10-1/4" / 6W / 228Lm

**043T-14-DB**

14-1/2" / 8W / 304Lm

**043T-22-DB**

22-1/2" / 13W / 494Lm

**043T-28-DB**

28-1/2" / 18W / 684Lm

**043T-32-DB**

32-1/2" / 24W / 912Lm



Priori T2 - Brushed Steel

**043T-10-BS**

10-1/4" / 6W / 228Lm

**043T-14-BS**

14-1/2" / 8W / 304Lm

**043T-22-BS**

22-1/2" / 13W / 494Lm

**043T-28-BS**

28-1/2" / 18W / 684Lm

**043T-32-BS**

32-1/2" / 24W / 912Lm



Priori T2 - White

**043T-10-WH**

10-1/4" / 6W / 228Lm

**043T-14-WH**

14-1/2" / 8W / 304Lm

**043T-22-WH**

22-1/2" / 13W / 494Lm

**043T-28-WH**

28-1/2" / 18W / 684Lm

**043T-32-WH**

32-1/2" / 24W / 912Lm

Each fixture includes (1) 3/8" clamp connector, (1) 3" linking cable and (2) mounting screws

## Priori T2 Accessories



**043J-WH** (White)

**043J-BR** (Bronze)

Hardwire junction box  
for PRIORI fixtures  
7-3/8"L x 2-1/8"W x 1"H  
Includes 12" extension and  
two 3/8" cable connectors  
c/UL/us Listed, dry



**043A-PC6-WH** (White)

**043A-PC6-BK** (Black)

6ft power cord  
for PRIORI fixtures  
120V AC grounded plug, 3-wire  
grounded moxex connector  
c/ETL/us Listed, dry



**043T-F06/30** 6 watt / 3000K / 90CRI

**043T-F08/30** 8 watt / 3000K / 90CRI

**043T-F13/30** 13 watt / 3000K / 90CRI

**043T-F18/30** 18 watt / 3000K / 90CRI

**043T-F24/30** 24 watt / 3000K / 90CRI

120V T2 fluorescent replacement lamp  
10,000hr rated life



**043A-6-EX-BK** 6"

**043A-12-EX-BK** 12"

**043A-24-EX-BK** 24"

**043A-36-EX-BK** 36"

Jumper (linking) Cables  
for PRIORI fixtures  
c/UL/us Listed, dry



**043A-6-EX-WH** 6"

**043A-12-EX-WH** 12"

**043A-24-EX-WH** 24"

**043A-36-EX-WH** 36"

Jumper (linking) cables  
for PRIORI fixtures  
c/UL/us Listed, dry