



LED A21



Ordering Information

Stock Code	Item name	Lumens ² (lm)	Watts (w)	CCT ¹ (k)	Efficacy (lm/w)	CRI	Beam Angle	Lifetime ³ (h)	Base type	Voltage (v)	Certification	Equivalent ⁴ (w)
PLT-10597	A21	1550	16	3000	97	80	240	10,000	E26	120	UL, CUL	100

Dimensions

Model	M.O.L.	Diameter
A21	5.30"	2.83"

Note: Lamp shape conforms to ANSI C78.21-2003.
 Note: Designed to comply with RoHS Directive 2002/95/EC.

Energy Savings

Model Number	Equivalent*	Energy Savings
L6-A2124U-16W-30	100W Incandescent	\$92

1. CCT Range complies to ANSI C78.377-2008.
2. Thermally stable typical lumens (± 10%)
3. Rated life is based on 70% lumen maintenance, and engineering testing and probability analysis.
4. Equivalency based on the Energy Star® Integral LED Lamp Center Beam Intensity Benchmark Tool.

Note: Energy Savings based on using one bulb for 10,000 hr rated life at 11¢/kWh.
 Does not include maintenance and replacement lamp savings.

*Actual Equivalent Replacement, based on the Energy Star® Integral LED Lamp Center Beam Intensity Benchmark Tool.