

FEATURES

- · Direct wire no ballast required
- Replaces 36W CFL PLL Lamps
- Simple installation

APPLICATION

This LED lamp is an efficient way to light sockets once traditionally reserved for compact fluorescents.

ELECTRICAL

Wattage	15W
Voltage	100-277V
Current	195mA
Power Factor	0.9
Total Harmonic Distortion (THD)	N/A

LIGHTING PERFORMANCE

Lumens	1200
Lumens Per Watt (Lm/W)	80
Color Temperature (CCT)	5000K
Color Rendering (CRI)	80
R9 (Red Value)	
R13 (Skin Tones)	
Beam Angle	120°
Light Distribution	
Dimmable Lighting Control	April 1000 April 2

ENVIRONMENT

Operating Temperature	-4° ~ 113°F		
Suitable Location	DAMP		
Ingress Protection Rating	IP20		
Suitable Fixture Type	Enclosed		

LIFESPAN

Average Life (Hours)	50,000
Warranty (Years)	5

COMPONENTS

LED Light Source	
------------------	--

CONSTRUCTION

Housing	Glass / PC	
Lens	Frost	
Base / Power Supply	2G11 / Plug In	

QUALIFICATIONS






Published lumens on LED products are approximate and may vary slightly.

Item#: **PLT-10775 LED PLL LAMP**

DIMENSIONS (Inches)

Length	16.3"
Width/Diameter	1.5"
Height	0.7"
Weight (Lbs)	

Line drawings may not be to scale and are for general reference only.



PACKAGING		UPC	DIMENSIONS (LxWxH)	GROSS WEIGHT (Lbs)
Master Carton	30	10811768029007		
Individual Box	1	811768029000	16."9 x 1.9" x 1.9"	0.5
Country of Origin	China			
HS Tariff	9405.40.8200			

ORDERING

ITEM#	DESCRIPTION	CASE
PLT-10775	LED PLL 15WT5/120°/FR/50K/2G11/100-277V	30