



## DATA SHEET

TAN-C5 LED extrusion – article number B5391 / B5391ANODA

### Product characteristics

The angular extrusion is made from high quality aluminum (also available in a double-anodized version) and is designed for flexible LED strips that are 8 - 12mm wide. LEDs can be hidden behind a special T cover made of polypropylene.

Standard polypropylene end caps and mounting brackets (made from steel, zinc or chrome finish) are used for the extrusion as supplementary accessories. End caps protect the extrusion from dust and other undesirable elements, which can make LED strips dirty and consequently deteriorate the lighting parameters.

The extrusion can be mounted to surfaces with the use of double-sided adhesive tape or mounting brackets. The mounting bracket guarantees easy and secure mounting of the extrusion to a desired surface and can also work as a connector between two extrusions.

### Applications

The extrusion with LED light source is mostly used as interior lighting, especially to light cabinets, stairs, glass-cases, or as a decoration light for a niche in drywall ceilings.

### Products related to the Extrusion



cover type T  
clear matte (17004)



end cap  
without hole (20052)



mounting bracket  
zinc (1399)  
chrome matt (1455)

### Technical specification

Ingress Protection Rating


IP 20

Available lengths

1 m / 2 m (can be cut to any size)

Material

body – aluminum, cover – polypropylene (PP), end cap – polypropylene (PP), mounting bracket – steel



\*sample item from the mounting system of profiles