



## DATA SHEET

TAMI LED extrusion – article number B5390 / B5390ANODA

### Product characteristics

The extrusion is made from high quality, standard or double-anodized aluminum and designed for flexible LED strips that are 8 - 12mm wide. LEDs can be hidden behind a special T cover made of polypropylene.

Standard polypropylene end caps are used for the extrusion as supplementary accessories. End caps protect the extrusion from dust and other undesirable elements, which can make LED strips dirty and consequently deteriorate the lighting parameters.

The extrusion can be mounted to surfaces with the use of double-sided adhesive tape or mounting brackets. The mounting bracket guarantees easy and secure mounting of the extrusion to a desired surface. It can also work as a connector between two extrusions. Installation of the profile in drywall is performed using special PDS springs. If you would like to mount a profile in an Armstrong drop ceiling with the use of PDS springs, we recommend special safety washers (42712).

### Applications

The extrusion with LED light source is mostly used as interior lighting, especially to light cabinets, stairs, glass-cases or as a decoration light for a niche in drywall ceilings.

### Products related to the Extrusion



cover type T  
clear matte (17004)



end cap  
without hole (20051)




mounting bracket  
zinc (1072)  
chrome matt (1345)



spring PDS (00800)

### Technical specification

Ingress Protection Rating	IP 20
Available lengths	1 m / 2 m (can be cut to any size)
Material	body – aluminum, cover – polypropylene (PP), end cap – polypropylene (PP), mounting bracket, spring – steel



\*sample item from the mounting system of profiles