

QUAD PLUG IN CFL



2 Pin Quad (Double) Tube CFL - Suitable for Preheat Magnetic Ballast

| Nominal Wattage | Model # | Generic Designation | Item Description & CCT | Lamp Base | Initial Lumen | Average Rated Life (Hrs.) | Length/ MOL (Inches/mm) | Pack Inner/ Master | Item # |
|-----------------|------------|---------------------|--------------------------|-----------|---------------|---------------------------|-------------------------|--------------------|--------|
| 13 | ODD13W/27K | CFQ13W/GX23/827 | 13W Quad CFL -2Pin-2700K | GX-23-2 | 860 | 10,000 | 4.7 / 120 | 25 / 100 | 012 |
| 13 | ODD13W/35K | CFQ13W/GX23/835 | 13W Quad CFL -2Pin-3500K | GX-23-2 | 860 | 10,000 | 4.7 / 120 | 25 / 100 | 013 |
| 13 | ODD13W/41K | CFQ13W/GX23/841 | 13W Quad CFL -2Pin-4100K | GX-23-2 | 860 | 10,000 | 4.7 / 120 | 25 / 100 | 014 |
| 18 | ODD18W/27K | CFQ18W/G24d/827 | 18W Quad CFL -2Pin-2700K | G24d2 | 1,200 | 10,000 | 6.2 / 157 | 25 / 100 | 017 |
| 18 | ODD18W/35K | CFQ18W/G24d/835 | 18W Quad CFL -2Pin-3500K | G24d2 | 1,200 | 10,000 | 6.2 / 157 | 25 / 100 | 018 |
| 18 | ODD18W/41K | CFQ18W/G24d/841 | 18W Quad CFL -2Pin-4100K | G24d2 | 1,200 | 10,000 | 6.2 / 157 | 25 / 100 | 019 |
| 26 | ODD26W/27K | CFQ26W/G24d/827 | 26W Quad CFL -2Pin-2700K | G24d3 | 1,800 | 10,000 | 7.0 / 178 | 25 / 100 | 022 |
| 26 | ODD26W/35K | CFQ26W/G24d/835 | 26W Quad CFL -2Pin-3500K | G24d3 | 1,800 | 10,000 | 7.0 / 178 | 25 / 100 | 023 |
| 26 | ODD26W/41K | CFQ26W/G24d/841 | 26W Quad CFL -2Pin-4100K | G24d3 | 1,800 | 10,000 | 7.0 / 178 | 25 / 100 | 024 |

4 Pin Quad (Double) Tube CFL - Suitable for Electronic Ballast

| | | | | | | | | | |
|----|-----------------|-----------------|---------------------------|-------|-------|--------|-----------|----------|-----|
| 13 | • ODD13W/4P/27K | CFQ13W/G24q/827 | 13W Quad CFL -4Pin -2700K | G24q1 | 900 | 12,000 | 5.3 / 135 | 25 / 100 | 015 |
| 13 | ODD13W/4P/35K | CFQ13W/G24q/835 | 13W Quad CFL -4Pin -3500K | G24q1 | 900 | 12,000 | 5.3 / 135 | 25 / 100 | 099 |
| 13 | • ODD13W/4P/41K | CFQ13W/G24q/841 | 13W Quad CFL -4Pin -4100K | G24q1 | 900 | 12,000 | 5.3 / 135 | 25 / 100 | 016 |
| 18 | • ODD18W/4P/27K | CFQ18W/G24q/827 | 18W Quad CFL -4Pin -2700K | G24q2 | 1,250 | 12,000 | 5.9 / 150 | 25 / 100 | 020 |
| 18 | ODD18W/4P/35K | CFQ18W/G24q/835 | 18W Quad CFL -4Pin -3500K | G24q2 | 1,250 | 12,000 | 5.9 / 150 | 25 / 100 | 100 |
| 18 | • ODD18W/4P/41K | CFQ18W/G24q/841 | 18W Quad CFL -4Pin -4100K | G24q2 | 1,250 | 12,000 | 5.9 / 150 | 25 / 100 | 021 |
| 26 | • ODD26W/4P/27K | CFQ26W/G24q/827 | 26W Quad CFL -4Pin -2700K | G24q3 | 1,800 | 12,000 | 6.7 / 171 | 25 / 100 | 025 |
| 26 | ODD26W/4P/35K | CFQ26W/G24q/835 | 26W Quad CFL -4Pin -3500K | G24q3 | 1,800 | 12,000 | 6.7 / 171 | 25 / 100 | 101 |
| 26 | • ODD26W/4P/41K | CFQ26W/G24q/841 | 26W Quad CFL -4Pin -4100K | G24q3 | 1,800 | 12,000 | 6.7 / 171 | 25 / 100 | 026 |

Applications



WALL SCONE



CEILING



TABLE/ FLOOR LAMPS



READING LAMP



RECESSED CANS



OUTDOOR COVERED



Features

- 10,000 to 12,000 hour average rated life reduces relamping & related costs
- Rare earth tri-phosphor with 80 plus CRI for better performance
- High Luminous Efficacy
- 75% Lower Power Consumption over incandescent bulbs
- Available in various color temperature
- Compact Size

Notes

- 4-Pin lamps are designed for Dimming & electronic applications
- Minimum Starting Temperature is also very much dependent on ballast.
- Available in various color temperature also (upon request)
- Equipment manufacturer are suggested to consult ANSI or IEC standard for maximum allowable dimensions & temperature for the optimum performance of the product.