

## GTR-AR-M21



### Description and Application:

LED Retrofit Kit for Outdoor Pole/Arm-Mounted Area and Roadway Luminaires

### Specification Features:

Available with Custom fitted aluminum plate, universal plate or universal bracket. Custom colors available upon request.

### Mounting Options:

- PLAT = Custom Plate
- UVSB = Universal Shoe Box Plate
- UVBR = Universal Bracket
- SOLY = Yoke Mount (E39)

### Driver and Wattage:

120-277vAC 60w input / 24vDC output  
120-277vAC 40w input / 24vDC output

### Additional Information:

Warranty:  
Driver - 5 year warranty  
Solstice Light Engine - 10 year warranty

LED And Optical Assembly:  
Structured LED Clusters for  
Optimized Photometric

Lumen Depreciation:  
System rating is L70 at  
100,000hrs.

Surge Protector:  
- Recommended for all outdoor  
applications

Ordering Code Example:

GTR-AR - M21 - LO - SV - GR - NL - PLAT

Fixture	LED Model #	Wattage Output	Diver Input Voltage	Color Temp	Optics	Mounting Method
GTR-AR	M21	LO = (30W)	SV = 120-277V	GR = 5000K (70CRI) BR = 5000K (80CRI)	NL = No Lens 360s = Square Side Emitters	PLAT UVSB
		ML = (40W)	SV = 120-277V	YW = 4100K (70CRI) BL = 4000K (80CRI)	T2 = Type II	UVBR SOLY
	M21	MH = (50W)	SV = 120-277V			
	M21	HI = (60W)	SV = 120-277V			



Fully Compliant with ARRA Buy American Requirements. Made in the USA.