

GTR-AR-5498



Description and Application:

LED Retrofit Kit for Outdoor Pole/Arm-Mounted Area and Roadway Luminaires

Specification Features:

- Available with Custom fitted aluminum plate, universal plate or universal bracket.
- Custom colors available upon request.

Mounting Options:

- PLAT = Custom Plate
- UVSB = Universal Shoe Box Plate
- UVBR = Universal Bracket
- SOLY = Yoke Mount (E39)

Driver and Wattage:

120-277vAC 150w input / 24vDC output
 120-277vAC 100w input / 24vDC output
 340-480vAC 150w input / 24vDC output
 340-480vAC 100w input / 24vDC output

Additional Information:

Warranty:
 Driver - 5 year warranty
 Solstice Light Engine - 10 year warranty

LED And Optical Assembly:
 Structured LED Clusters for
 Optimized Photometric

Lumen Depreciation:
 System rating is L70 at
 100,000hrs.

Surge Protector:
 - Required for ALL 347V-480V applications in order to qualify for Warranty
 - Recommended for all outdoor applications

Ordering Code Example:

GTR-AR - 5498 - HO - SV - GR - NL - PLAT

| Fixture | LED Model # | Wattage Output | Diver Input Voltage | Color Temp | Optics | Mounting Method |
|---------|-------------|----------------|---------------------|--------------------|-----------------------------|-----------------|
| GTR-AR | 5498 | ML = (75W) | SV = 120-277V | GR = 5000K (70CRI) | NL = No Lens | PLAT |
| | | | HV = 347-480V | BR = 5000K (80CRI) | 360s = Square Side Emitters | UVSB |
| | 5498 | MH = (85W) | SV = 120-277V | YW = 4100K (70CRI) | T2 = Type II | UVBR |
| | | | HV = 347-480V | BL = 4000K (80CRI) | | SOLY |
| | 5498 | HI = (95W) | SV = 120-277V | | | |
| | 5498 | HO = (135W) | SV = 120-277V | | | |
| | | | HV = 347-480V | | | |



Fully Compliant with ARRA Buy American Requirements. Made in the USA.