



Dimmable LED BR20



3 THREE YEARS WARRANTY

Ordering Information

Stock Code	Item name	Lumens ² (lm)	Watts (w)	CCT ¹ (k)	Efficacy (lm/w)	CRI	Beam Angle	Lifetime ³ (h)	Base type	Voltage (v)	Certification	Equivalent ⁴ (w)
PLT-10599	BR20	550	7	2700	79	80	-	25,000	E26	120	UL, CUL	50

Compatible Dimmer List:**

- AH SDM3/1000/WHTTE
- ALMOND LUXDM600-12
- CTL DM600-12-3
- GE 18024
- LEVITON 603-6631-A
- LEVITON 6631-A
- LEVITON 6631-LA
- LEVITON NO.6672
- LEVITON IPI06-1LZ
- LEVITON S-600P-WH
- LUTRON D-600R-WH
- LUTRON DV-600PH-WH
- LUTRON DV-603P
- LUTRON DV-603PH-WH
- LUTRON DV-603PH-WH
- LUTRON DV-603PR
- LUTRON S-600-AL
- LUTRON S-600-IV
- LUTRON S-600PR-WH
- LUTRON S-603PH-WH
- LUTRON TG-600PH-WH

Dimensions

Model	M.O.L.	Diameter
BR20	3.82"	2.50"

Note: Lamp shape conforms to ANSI C78.21-2003.
 Note: Designed to comply with RoHS Directive 2002/95/EC.

Energy Savings

Model Number	Equivalent*	Energy Savings
L4-BR20D-7W-27	50W Incandescent	\$118

1. CCT Range complies to ANSI C78.377-2008.
2. Thermally stable typical lumens (± 10%)
3. Rated life is based on 70% lumen maintenance, and engineering testing and probability analysis.
4. Equivalency based on the Energy Star® Integral LED Lamp Center Beam Intensity Benchmark Tool.

Note: All Information consistent with IESNA LM-80-08 results and IESNA LM-79-08 testing completed by a qualified third party facility.
 Note: All lamps meet Energy Star® Integral LED Lamp requirements, and will be submitted for testing.
 Note: Energy Savings based on using one bulb for 25,000 hr rated life at 11¢/kWh.
 Does not include maintenance and replacement lamp savings.

*Actual Equivalent Replacement, based on the Energy Star® Integral LED Lamp Center Beam Intensity Benchmark Tool.
 **Tested to a maximum of 18 lamps per dimmer with proper functioning.